NTC Ring Temperature Sensor Cable Assemblies



Molex's Temperature Sensor Cable Assemblies are available in a variety of beta values, resistances, lengths and temperature ranges to meet a diverse range of applications. The NTC Ring and Epoxy Coated Temperature Sensor Cable Assemblies include a ring terminal, thermal conductive epoxy and/or a Micro-Lock PLUS connector to deliver a market-ready solution for temperature sensing



Reference Data

Reference Data		
PARAMETER	OPTIONS	UNIT
Resistance @ 25°C	1, 2.25, 3, 4.7, 5, 10, 12, 20, 30, 47, 50, 100	kohms
Resistance Tolerance	1, 2, 3, 5	%
Operating Temperature Range	-40 to +150; -40 to +105	°C
Dissipation Constant (in air)	3.2	mW/K
Thermal Time Constant	5	S
Temperature Coefficient Resistance	-4.4	%/°C
Max Power	100	mW
Mounting Hole Diameter	M2, M3.5, M4	mm
Beta Value @ B25/85	3500, 3802, 3964, 3982, 4050, 3892, 4035, 3600	К
Molex Connector	5055650201	

NTC Ring Temperature Sensor Cable Assemblies

molex

Markets and Applications

Consumer

Vending machines ATMs

Computers

Printing machines

Home Appliance

Refrigerators

Electric Ovens

Freezers

Coffee makers

Industrial

HVAC

Motors





Note: Molex reserves the right to delay or cancel production of the depicted product without additional notice. Please contact your Molex customer service representative for product availability.

www.molex.com/link/temperaturesensorcableassemblies.html

Molex is a registered trademark of Molex, LLC in the United States of America and may be registered in other countries; all other trademarks listed herein belong to their respective owners.