

KP HCS T-MIC K12 C3 P9 - Membrane keypad



2203567

<https://www.phoenixcontact.com/us/products/2203567>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Membrane keypad, self-adhesive, silver conduction technology, 12 keys, embossed, 3 colors, connecting cable: 88.5 mm, with crimp female connector, pitch: 2.54 mm, operating temperature: -20°C ... 70°C

Your advantages

- Easy integration into HCS series electronics housings
- Membrane keypads in various sizes and colors for customized device designs
- Customization of membrane keypad via configurator

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 2203567 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | AC02 |
| Product key | ACFABF |
| GTIN | 4055626474007 |
| Weight per piece (including packing) | 13.5 g |
| Weight per piece (excluding packing) | 13.5 g |
| Customs tariff number | 85371098 |
| Country of origin | DE |

KP HCS T-MIC K12 C3 P9 - Membrane keypad



2203567

<https://www.phoenixcontact.com/us/products/2203567>

Technical data

Product properties

| | |
|-----------------------|---|
| Product type | Membrane keypad |
| Housing type | Handheld housing |
| Housing series | HCS |
| Product family | HCS |
| Number of positions | 9 |
| Pitch | 2.54 mm |
| Technology | Conductive silver/graphite (T6/4 Cu/Ag) |
| Embossing | Dome embossing 10 x 10 mm |
| Number of socket pins | 9 |
| Number of keys | 12 (2 x 6) |

Dimensions

| | |
|------------|--------------------------|
| Length | 88.5 mm (Membrane cable) |
| Pitch | 2.54 mm |
| Dimensions | 38 mm x 140 mm |

Material specifications

| | |
|------------------|-----------|
| Housing material | Polyester |
|------------------|-----------|

Environmental and real-life conditions

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -20 °C ... 70 °C |
| Ambient temperature (storage/transport) | -40 °C ... 80 °C |

Mounting

| | |
|---------------|----------|
| Mounting type | adhesive |
|---------------|----------|

KP HCS T-MIC K12 C3 P9 - Membrane keypad



2203567

<https://www.phoenixcontact.com/us/products/2203567>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27182702 |
| ECLASS-13.0 | 27190605 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC001031 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 31261500 |
|-------------|----------|

KP HCS T-MIC K12 C3 P9 - Membrane keypad



2203567

<https://www.phoenixcontact.com/us/products/2203567>

Environmental product compliance

| | |
|---|--|
| EU RoHS | |
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
| China RoHS | |
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |
| EU REACH SVHC | |
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

KP HCS T-MIC K12 C3 P9 - Membrane keypad



2203567

<https://www.phoenixcontact.com/us/products/2203567>

Accessories

HCS-T MICRO X C 1 1 7035 - Electronics housing

2203126

<https://www.phoenixcontact.com/us/products/2203126>



Handheld housing, T-Micro, light gray, consisting of two half shells, two front plates with screws, front 1.1 mm recessed, closed with keypad slot

HCS-T MICRO X 2AA C C 7035 - Electronics housing

2203127

<https://www.phoenixcontact.com/us/products/2203127>



Handheld housing, T-Micro, light gray, consisting of two half shells, screws, front 1.1 mm recessed, closed with keypad slot, battery compartment cover and battery contacts, for 2 AA batteries

KP HCS T-MIC K12 C3 P9 - Membrane keypad



2203567

<https://www.phoenixcontact.com/us/products/2203567>

HCS-T MICRO X 2AA 1 1 7035 - Electronics housing

2203128

<https://www.phoenixcontact.com/us/products/2203128>



Handheld housing, T-Micro, light gray, consisting of two half shells, two front plates, screws. Front 1.1 mm recessed, closed with keypad slot, battery compartment cover and battery contacts for 2 AA batteries

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com