



Part Number : 476030001

Series Number : 47603

Product Category : Memory / SIM Card Connectors


Product Description : 1.27mm Pitch SIM Card Holder with 2 Detect Pins, 8 Circuits, Push-Push Style, Housing Height 1.90mm, without Pegs, Lead-Free

Status : New Business Not Supported

Documents & Resources

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	New Business Not Supported
--------	----------------------------

Category	Memory / SIM Card Connectors
Series	47603
Description	1.27mm Pitch SIM Card Holder with 2 Detect Pins, 8 Circuits, Push-Push Style, Housing Height 1.90mm, without Pegs, Lead-Free
Comments	Without Pegs
Product Family	SD and SIM Memory Card Sockets
Product Name	mini-SIM
Style	Push-Push
UPC	800756792262

Electrical

Current - Maximum per Contact	0.5A
Shielded	Yes
Voltage - Maximum	50V DC

Physical

Card Detection Switch	Closed
Card Entry Location	Front
Circuits (Loaded)	8
Circuits (maximum)	8
Durability (mating cycles max)	5000
Ejector Button Side	N/A
Material - Contact	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Gold
Material - Resin	High Temperature Thermoplastic
Material - Shell	Stainless Steel
Net Weight	1.498/g
Packaging Type	Embossed Tape on Reel
PCB Locator	No
PCB Retention	Yes
Pitch - Mating Interface	1.27mm
Pitch - Termination Interface	1.27mm
Temperature Range - Operating	-20° to +70°C

Termination Interface Style	Surface Mount
-----------------------------	---------------

Solder Process Data

Max-Duration	3
Lead-Free Process Capability	REFLOW
Max-Cycle	2
Max-Temp	250