

	1	2	3	4	5	6	7																																																																																					
A	Technical Data Material: Pin (outer sleeve): Brass, machined, CuZn38Pb2 Clip (contact 4 finger): Beryllium copper heat treated Plating (outer sleeve): 2um/80u"nickel, 5um/200u"Tin Plating clip(contact): 2um/80u"nickel, Gold Flash Electrical Current rating: 3 Amps/contact max. Contact resistance: ≤ 4mΩ /contact Mechanical Operating temperature: -40°C to +105°C Mechanical life: min.200							A																																																																																				
B								B																																																																																				
C								C																																																																																				
D								D																																																																																				
E								E																																																																																				
F								F																																																																																				
G	RoHS compliant Unit: mm <table><tr><th>Scale</th><th>Free</th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>TOLERANCE</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>X.</td><td>±0.20</td><td></td><td></td><td></td><td>Drawn</td><td>27.08.2009</td><td>Dean</td></tr><tr><td>X.X</td><td>±0.15</td><td></td><td></td><td></td><td>Approved</td><td>28.10.2016</td><td>Amy</td></tr><tr><td>X.XX</td><td>±0.10</td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>X.XXX</td><td>±0.05</td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>DIM</td><td>TOL</td><td>②</td><td>Update to new drawing</td><td>28.10.2016</td><td>Amy</td><td></td><td></td></tr><tr><td>Angle</td><td>±5°</td><td>①</td><td>Drawn</td><td>27.08.2009</td><td>Dean</td><td></td><td></td></tr><tr><td>Angle</td><td>TOL</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td></td><td></td></tr></table> WSW components <table><tr><td>Drawing-No.</td><td>ASSMANN WSW-No.</td><td>Customer-No.</td></tr><tr><td>ASS 3669 CO</td><td>APC XX-A</td><td></td></tr><tr><td>Replace</td><td></td><td></td></tr><tr><td>Sheet 1 / 2</td><td></td><td></td></tr></table>							Scale	Free							TOLERANCE								X.	±0.20				Drawn	27.08.2009	Dean	X.X	±0.15				Approved	28.10.2016	Amy	X.XX	±0.10							X.XXX	±0.05							DIM	TOL	②	Update to new drawing	28.10.2016	Amy			Angle	±5°	①	Drawn	27.08.2009	Dean			Angle	TOL	Id.	Modification	Date	Name			Drawing-No.	ASSMANN WSW-No.	Customer-No.	ASS 3669 CO	APC XX-A		Replace			Sheet 1 / 2			G
Scale	Free																																																																																											
TOLERANCE																																																																																												
X.	±0.20				Drawn	27.08.2009	Dean																																																																																					
X.X	±0.15				Approved	28.10.2016	Amy																																																																																					
X.XX	±0.10																																																																																											
X.XXX	±0.05																																																																																											
DIM	TOL	②	Update to new drawing	28.10.2016	Amy																																																																																							
Angle	±5°	①	Drawn	27.08.2009	Dean																																																																																							
Angle	TOL	Id.	Modification	Date	Name																																																																																							
Drawing-No.	ASSMANN WSW-No.	Customer-No.																																																																																										
ASS 3669 CO	APC XX-A																																																																																											
Replace																																																																																												
Sheet 1 / 2																																																																																												
H								H																																																																																				
1	2	3	4	5	6	7																																																																																						

	1	2	3	4	5	6	7	
A	② Technical Data Material: Pin (outer sleeve): Brass,machined, CuZn38Pb2 ②Clip (contact 4 finger): Beryllium copper heat treated Plating (outer sleeve): 2um/80u"nickel,5um/200u"Tin Plating clip(contact): 2um/80u"nickel,Gold Flash Electrical Current rating: 3 Amps/contact max. Contact resistance: ≤ 4mΩ /contact Mechanical Operating temperature: -40°C to +105°C Mechanical life: min.200							A
B								B
C								C
D								D
E								E
F	RoHS compliant Unit: mm							F
G								G
H								H
	1	2	3	4	5	6	7	