



# Serial ATA (SATA) Latching Signal Cable (7Pin/7Pin), 12-in. (30.48 cm)

MODEL NUMBER: P940-12I



#### **Features**

- Connect your high-speed Serial ATA device to a Serial ATA controller
- · Compatible with Serial ATA Hard Drives, Blu-ray/DVD/CD Drives and other Serial ATA devices
- Metal latches ensure secure connections
- Support data transfer rates of up to 6.0 Gbps
- Narrow cables design simplifies cable routing and installation and improves air flow within CPU (no more big ribbons blocking air movement)
- Meets Serial ATA 1.0 standards, including Errata 029
- Cable is shielded to protect against EMI/RFI

# **Highlights**

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Support data transfer rates of up to 6.0 Gbps
- Cable is shielded to protect against EMI/RFI

# **Applications**

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Compatible with Serial ATA Hard Drives, Blu-ray/DVD/CD Drives and other Serial ATA devices

# **System Requirements**

- Serial ATA device
- Serial ATA controller

# **Package Includes**

• 12-in. Serial ATA (SATA) Latching Signal Cable 7Pin/7Pin, Straight/Straight

# **Specifications**

| OVERVIEW                  |                            |  |
|---------------------------|----------------------------|--|
| UPC Code                  | 037332184382               |  |
| Technology                | SATA/eSATA                 |  |
|                           |                            |  |
| CONNECTIONS               |                            |  |
| Side A - Connector 1      | 7 PIN SATA STRAIGHT (MALE) |  |
| Side B - Connector 1      | 7 PIN SATA STRAIGHT (MALE) |  |
|                           |                            |  |
| PHYSICAL                  |                            |  |
| Color                     | Red                        |  |
| Cable Jacket Color        | Red                        |  |
| Cable Outer Diameter (OD) | 2.4/8.0mm                  |  |





| Wire Gauge (AWG)                       | 26                        |  |
|--|---------------------------|--|
| Cable Length (ft.)                     | 1                         |  |
| Cable Length (m)                       | 0.30                      |  |
| Cable Length (in.)                     | 12                        |  |
| Cable Length (cm)                      | 30.48                     |  |
| Shipping Dimensions (hwd / in.)        | 0.12 x 4.00 x 6.00        |  |
| Shipping Dimensions (hwd / cm)         | 0.32 x 10.16 x 15.24      |  |
| Shipping Weight (lbs.)                 | 0.04                      |  |
| Shipping Weight (kg)                   | 0.02                      |  |
| Unit Dimensions (hwd / in.)            | 0.125 x 4.000 x 6.000     |  |
| FEATURES & SPECIFICATIONS              |                           |  |
| IP68 Rated                             | No                        |  |
| IP20 Rated                             | No                        |  |
| STANDARDS & COMPLIANCE                 |                           |  |
| Product Compliance                     | RoHS                      |  |
| WARRANTY & SUPPORT                     |                           |  |
| Product Warranty Period<br>(Worldwide) | Lifetime limited warranty |  |

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.