SFP28 | DWDM

TE Internal #: 1367645-4


SFP, Cage Assembly, Signal, Operating Temperature Range -55 – 85 °C [-67 – 185 °F], Data Rate (Max) 4 Gb/s, 20 Position, 1 Ports

View on TE.com >




Connectors > Pluggable IO Connectors & Cages > SFP Connectors











Pluggable I/O Product Type: Cage Assembly

Sealable: No

Circuit Application: Signal

Operating Temperature Range: -55 - 85 °C [-67 - 185 °F]

Data Rate (Max): 4 Gb/s

All SFP Connectors (10)

Features

Product Type Features

Thermal Accessory Type Included	Heat Sink
Cage Type	Single
Pluggable I/O Product Type	Cage Assembly
Sealable	No
Form Factor	SFP

Configuration Features

Number of Positions	20
Number of Ports	1
Port Matrix Configuration	1 × 1

Electrical Characteristics

Data Rate (Max) 4 Gb/s	
------------------------	--

Body Features

.165 in



Heat Sink Height Class	PCI
Heat Sink Style	Pin
Termination Features	
Termination Post & Tail Length	3 mm[.118 in]
Termination Method to Printed Circuit Board	Through Hole - Press-Fit
Housing Features	
Cage Material	Copper Alloy
Dimensions	
PCB Thickness (Recommended)	2.25 mm[.089 in]
Usage Conditions	
Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]
Operation/Application	
Pluggable I/O Applications	SFP
Heat Sink Compatible	Yes
Circuit Application	Signal
Packaging Features	
Packaging Method	Box & Tray
Other	
Included Lightpipe	No
EMI Containment Feature Type	Internal/External EMI Springs

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free



Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # CAT-SF59-C76264
SFP Connectors



TE Part # 1367147-1 SFP COVER, UNPLATED




TE Part # 1367147-3 SFP COVER, UNPL, NO LOGO



TE Part # 1761394-1
DUST COVER, SFP, GANGED &
STACKED



Also in the Series | DWDM



Customers Also Bought

04/27/2024 04:27AM | Page 3





TE Part #6469083-1 HMZD 3PAIR, HDR ASSY, 25MM MOD



TE Part #1-329632-2 LOCKWASHER, PLATED



TE Part #3-1827231-6 .5FHR04H,440,B,GIG,08/Sn,HT,NS






TE Part #1551920-2 zQSFP+ connector assembly



TE Part #1658621-9
40 NOVO MIL/CTR 15DP,LEAD FREE




TE Part #5536507-1 2MM FB,ASY,24,SIG,REC,SL,2.73



M5B0



TE Part #214782-E
EPSVA KS GDM4 EE 10 3,8 SN *
STROMVERSOR



Documents

Product Drawings

DWDM Kit Assy, PCI (4.2)

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1367645-4_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1367645-4_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1367645-4_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

SFP, Cage Assembly, Signal, Operating Temperature Range -55 – 85 °C [-67 – 185 °F], Data Rate (Max) 4 Gb/s, 20 Position, 1 Ports



Product Specification

English