

SFP28 | XFP

TE Internal #: 2303075-2

XFP, Cage Assembly, Sealable, Signal, Operating Temperature Range -10 – 70 °C [-14 – 158 °F], Data Rate (Max) 10 Gb/s, 1 Ports

View on TE.com >



Connectors > Pluggable IO Connectors & Cages > XFP Cage Assemblies and Kits



Pluggable I/O Product Type: Cage Assembly

Sealable: Yes

Circuit Application: Signal

Operating Temperature Range: -10 - 70 °C [-14 - 158 °F]

Data Rate (Max): 10 Gb/s

All XFP Cage Assemblies and Kits (22)

Features

Product Type Features

Cage Type	Single
Pluggable I/O Product Type	Cage Assembly
Sealable	Yes
Form Factor	XFP

Configuration Features

Number of Ports	1	
Port Matrix Configuration	1 × 1	

Electrical Characteristics

Data Rate (Max)	10 Gb/s
-----------------	---------

Body Features

Heat Sink Finish	Electroless Nickel
	.255 in
Heat Sink Height Class	SAN
Heat Sink Style	Pin
Cage Plating Material	Tin

Termination Features



Termination Post & Tail Length	2.05 mm[.08 in]
Termination Method to Printed Circuit Board	Through Hole - Press-Fit
Housing Features	
Cage Material	Copper Alloy
Dimensions	
Product Width	64.03 mm[2.52 in]
Product Length	21.7 mm[.854 in]
Usage Conditions	
Operating Temperature Range	-10 - 70 °C[-14 - 158 °F]
Operation/Application	
Heat Sink Compatible	Yes
Circuit Application	Signal
Packaging Features	
Packaging Method	Tray
Other	
Included Lightpipe	No
EMI Containment Feature Type	Elastomeric Gasket

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer




This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts






Also in the Series | XFP







Customers Also Bought



















Documents

Product Drawings

XFP KIT W/CAGE, CLIP, HEAT SINK, SAN

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2303075-2_1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2303075-2_1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2303075-2_1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English