2349201-6 - ACTIVE

SFP56

TE Internal #: 2349201-6 zSFP+ Stacked (SFP56), Cage Assembly with Integrated Connector, .018in [.6mm] Centerline, Signal

View on TE.com >



Connectors > Pluggable IO Connectors & Cages > SFP56 Stacked Cage Assembly: EMI Spring



Pluggable I/O Product Type: Cage Assembly with Integrated Connector

Centerline (Pitch): .6 mm [.018 in]

Circuit Application: Signal

Operating Temperature Range: -55 – 105 °C [-67 – 221 °F]

Data Rate (Max): 56 Gb/s

All SFP56 Stacked Cage Assembly: EMI Spring (48)



Features

Product Type Features

| Cage Туре | Stacked | |
|---|---|--|
| Pluggable I/O Product Type | Cage Assembly with Integrated Connector | |
| Form Factor | zSFP+ Stacked (SFP56) | |
| Configuration Features | | |
| Number of Positions | 20 | |
| Number of Ports | 24 | |
| Port Matrix Configuration | 2 x 12 | |
| Electrical Characteristics | | |
| Data Rate (Max) | 56 Gb/s | |
| Termination Features | | |
| Termination Method to Printed Circuit Board | Through Hole - Press-Fit | |
| Housing Features | | |
| Centerline (Pitch) | .6 mm[.018 in] | |

C For support call+1 800 522 6752

2349201-6

zSFP+ Stacked (SFP56), Cage Assembly with Integrated Connector, .018in [.6mm] Centerline, Signal



| Usage Conditions | |
|--|--|
| Operating Temperature Range | -55 – 105 °C[-67 – 221 °F] |
| Operation/Application | |
| Pluggable I/O Applications | SFP28 |
| Circuit Application | Signal |
| Other | |
| Included Lightpipe | Yes |
| | |
| EMI Containment Feature Type | Internal/External EMI Springs |
| EMI Containment Feature Type Product Compliance For compliance documentation, visit the product page on TE.com> | Internal/External EMI Springs |
| Product Compliance | Internal/External EMI Springs Compliant |
| Product Compliance For compliance documentation, visit the product page on TE.com> | |
| Product Compliance For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU | Compliant |

Does not contain REACH SVHC

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

2349201-6

zSFP+ Stacked (SFP56), Cage Assembly with Integrated Connector, .018in [.6mm] Centerline, Signal





TE Part # 1761394-1 DUST COVER, SFP, GANGED & STACKED

Also in the Series | SFP56



Customers Also Bought



| TEL | -= TE | = TE | |
|--|---|---|--|
| TE Part #2349202-5 SFP56 STACKED 2X1 RECEPTACLE ASSEMBLY | TE Part #6-2213362-2 RCPT ASSY,DIMMABLE PHOTOCONTROL,150C,3 P | TE Part #1-2170287-1 1X4 CAGE ASSEMBLY, QSFP,SINGLE SQ LP | TE Part #1734100-3 Champ050 series,30pos,Au over PdNi |
| | ETE | | |

 TE Part #1734101-3
 TE Part #1934949-1
 TE Part #2007808-2

 Champ050 series,30pos,Au over PdNi
 Tinman 5pr 8col vert recpt 15mm stack
 IMP100S,H,V4P10C,LG,OEW46,4.9

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2349201-6_A.2d_dxf.zip

English

2349201-6

zSFP+ Stacked (SFP56), Cage Assembly with Integrated Connector, .018in [.6mm] Centerline, Signal



Customer View Model ENG_CVM_CVM_2349201-6_A.3d_igs.zip

English

Customer View Model ENG_CVM_CVM_2349201-6_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Application Specification

English