GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: High Power DC Connectors, , Efficiency Level: , Case Color/Style: GlobTek Black, , , Input Rating: , , Output Rating: W, 0.0V@0.0A, Output Configuration: mm, / Cond, , , Ferrite: , , GT Cord # , Pin Out: , Blades/Input Cord: , Approvals: to , GT Cab Model No. High Power DC Connectors				
	Part No./Ordering No. JACK-L-SMT-10A-RA(R)	Rev B2			

In Addition to GlobTek Inc.'s renewed ISO9001:2008 - Quality Management System Certification, GlobTek Inc. is now certified to:

ISO13485:2003 - Medical Devices Quality Management System Certification ISO14001:2004 - Environmental Management System Certification

ISO Certificates are available online at http://www.globtek.com/iso-certificates/

The acceptance of this specification and use of the product described in this document indicates the acceptance and binding of the customer to Globtek TERMS AND CONDITIONS (attached to the end of this document), which supersede all other agreements, terms, and conditions (http://www.globtek.com/terms-and-conditions/).

Prop 65 Statement:https://www.globtek.com/prop-65-statement.pdf

Footnote:

GlobTek Inc. will not be liable for the safety and performance of these power supplies if unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instruction.

Limitation of Use:

GlobTek products are intended for use with commercial, medical, and/or industrial equipment only. GlobTek product are not authorized for use as mission critical components in life support hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of GlobTek Inc.

Contents of this document are subject to change without prior notice.

Customer Approval of Specification:

Please approve, sign and send back to GlobTek so we can complete order processing. A delay in receipt of this form will delay delivery schedule.

Company Name:	Customer P/N:
Quote Number:	Date:
Authorized Representative Name:	Authorized Representative Signature:

PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2018 - 2024 guest /05/18/2024 8:26:36 AM CLONED FROM JACK-C-PC-10A-RA(R)

GlobTek, Inc.
www.globtek.com
186 Veterans Drive,
Northvale, NJ 07647
Tel. (201) 784-1000
Fax (201) 784-0111

Drawing Title: High Power DC Connectors, , Efficiency Level: , Case Color/Style: GlobTek Black, , , Input Rating: , , Output Rating: W, 0.0V@0.0A, Output Configuration: mm, / Cond, , , Ferrite: , , GT Cord # , Pin Out: , Blades/Input Cord: , Approvals: to , GT Cab

Model No. High Power DC Connectors

Part No./Ordering No. JACK-L-SMT-10A-RA(R)

Rev B2

REV	DESCRIPTION					SUB	DATE	APPROVED
B2	Update the datasheet to add "Similar to: " and "Mates with:"					QA	01/23/2024	QA
B1	Correct pinout drawing					QA	03/17/2023	QA
В	Update drawing					QA	01/07/2022	QA
A1	Update to SF format, add tab mater	ial and plating				QA	11/03/2021	QA
А	Initial release					QA	08/16/2018	QA
3D CAE								
	en.globtek.com/pdf/JACK-L-SM CY ONLINE DOCUMENTS	I-10A-RA(R).stp						
	RoHS3 Declaration	https:/	www.alob	ek.com/pdf/rol	ns_cert/01t0c00	0008nDt	ΟΑΑΙΙ	
	Declaration				_certificates/RI			
	t Minerals Declaration							
Prop 65	5 Statement							
IPXY ra	ating is based on 3rd party testir	ig and customers	should che	eck suitability a	nd test system	level IPX	Y rating before orde	ering.
	5.6 7.2 5.8 PCBLAYOUT TOP VIEW 13.8	13.8	4	MATER	AL PLATING nickel			
	4.1 2-2x1 1.8x1		2 0	letal case copper uter spring contact copper lastic PPA ins copper	nickel nickel Bright tin (optional n	latte tin)		
3 2 4.11.2 4.11.2 1.4x1		SPECIFICATIONS parameter rated input voltage rated input current contact resistance insulation resistance voltage withstand Relative humidity life	3	ons/description Hz for 1 minute 1500	50 10 30 100	mΩ MΩ Vac		
Similar	to: RASM712X KLDHCX-M	M-0202-BTR 54	-00254 P	J-068B-SMT-T	R PJ-069B-SI	ИТ-Т		
Mates w	vith: T-L-95-S(R) T-L-12-S(R) T-L-14-S(R)	760 765	KLDX-PA-020	2-B PP3-002	3 55-00	050 EP501B 48	40.1210
		,	00 100		20110-002			19.1210

guest /05/18/2024 8:26:36 AM CLONED FROM JACK-C-PC-10A-RA(R)

GlobTek, Inc. www.globtek.com 186 Veterans Drive,	Drawing Title: High Power DC Connectors, , Efficiency Level: , Case Color/Style: GlobTek Black, , , Input Rating: , , Output Rating: W, 0.0V@ Configuration: mm, / Cond, , , Ferrite: , , GT Cord # , Pin Out: , Blades/Input Cord: , Approvals: to , GT Cab Model No. High Power DC Connectors	0.0A, Output 0
Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Part No./Ordering No. JACK-L-SMT-10A-RA(R)	Rev B2

PACKAGING

Packing Spec P/N:	
Box Qty:	1000
Gift Box Size (mm):	
Gift Box Color:	White
Master Carton Size (mm):	TBD
Master Carton Cubic Volume (m ³):	0.00
Master GW (Kg):	kg
wt Ea. (Kg):	kg
wt Ea. (Kg):	kg
LABEL SPECS: Standard GT,L-11	86
PACK SPEC:	