

CyberPower

CSP806U | PROFESSIONAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The Professional Surge Protector CSP806U from CyberPower offers vital surge protection for common home and office devices such as computers and electronics. It prevents spikes in energy caused by storms and electrical power surges and is ideal for safeguarding personal computers, phones/faxes/modems, and other consumer electronics. The CSP806U provides 3,000 joules of protection and eight surge-protected outlets. Its two USB charge ports (2.4 Amp shared) keep tablets, smartphones, and other rechargeable electronics ready to use. The 6-ft. power cord has a right-angle plug with a 45° offset.

Features of the CSP806U include automatic shutdown, metal oxide varistor (MOV) technology, and an EMI/RFI noise filter. It also has LED indicators (Protected and Grounded), and impact-resistant casing. The CSP806U comes with a One-Year Limited Warranty and a \$300,000 Connected Equipment Guarantee.



TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

FEATURES

- Surge suppression: 3,000 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P (45° offset)
- Outlet type: 8 NEMA 5-15R (surge-protected)
- Power cord: 6 ft.
- USB charge ports: 2
- LED indicator: Yes
- Keyhole slots: No
- EMI/RFI Filtration: Yes
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$300,000

SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	6 ft (1.8 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A

OUTPUT	
Outlet Type	8 - NEMA 5-15R
Outlets - Total	8
Outlets - Widely Spaced	2
USB Charge Port	Yes
USB Charge Port Amperage	2.4 A (Shared)
USB Charge Port Quantity	2
USB Charge Port Type	Type A
USB Charge Port Voltage	5 VDC

CSP806U

PROFESSIONAL SURGE PROTECTOR

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING	
Attenuation	30 dB
Clamping Voltage	600V (H-N, H-G, N-G)
Coax Protection RG6	None
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	105,000 A
Maximum Surge Current H-G	30,000 A
Maximum Surge Current H-N	45,000 A
Maximum Surge Current N-G	30,000 A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	3,000 J
PHYSICAL	
Color	White
Cord Management	No
Form Factor	Strip
Material of Construction	Plastic
Safety Covers	No

PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	9.91 x 3.99 x 19.81 cm
Physical Dimensions - Width/Height/Depth (mm)	99 x 40 x 198 mm
Physical Dimensions - Width/Height/Depth (in.)	3.9 x 1.57 x 7.8 in.
Weight (kg)	0.60 kg
Weight (lb)	1.32 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	16.48 x 4.6 x 26.49 cm
Shipping Dimensions - Width/Height/Depth (mm)	164.85 x 45.97 x 264.92 mm
Shipping Dimensions - Width/Height/Depth (in.)	6.49 x 1.81 x 10.43 in.
Shipping Weight (kg)	0.85 kg
Shipping Weight (lbs.)	1.87 lbs.

CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1363 UL1449 3rd Edition cUL

WARRANTY	
CEG Amount	\$300,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited Warranty