



# 16-Outlet 1U Rack-Mount AC Charger Power Strip, 120V, 15A, 15 ft. (4.57 m) Cord

MODEL NUMBER: PS1916D1U









Charges up to 16 notebooks, netbooks, tablets or other battery-intensive electronic devices that use a NEMA 5-15P power adapter. Can be mounted in 1U of rack space for out-of-the-way convenience.

#### **Description**

The PS1916D1U 16-Outlet 1U Rack-Mount AC Charger Power Strip provides high-speed charging for up to 16 mobile devices simultaneously, such as notebooks, netbooks, tablets and other battery-intensive electronics that use a NEMA 5-15P plug.

This power strip features 16 built-in NEMA 5-15R AC outlets attached to convenient dongles that easily accommodate large transformer plugs. It's compatible with all devices that charge via standard AC outlets (such as Chromebooks, MacBook Airs and Ultrabooks) or user-supplied USB power adapters (such as smartphones, iPads, Kindles, Kindle Fires and Surface models).

The all-steel PS1916D1U mounts into 1U of two- or four-post rack space using the included hardware. The NEMA 5-15P input plug is attached to a 15-ft. (4.57 m) power cord long enough to reach a PDU or AC wall outlet. A 15-amp circuit breaker protects against overloads and short circuits. A transparent cover guards the lighted on/off switch from accidental shutdowns.

#### **Features**

#### Charges Up to 16 Electronic Devices at the Same Time

- Compatible with all devices that charge via standard AC outlets, including Chromebooks, MacBook Airs and Ultrabooks
- Compatible with all devices that charge via user-supplied USB adapters, including smartphones, iPads, Kindles, Kindle Fires and Surface tablets
- Convenient dongles easily accommodate large transformer plugs

#### Keeps Equipment Safe and Secure

- 15A circuit breaker protects against overloads and short circuits
- Transparent cover guards lighted on/off switch from accidental shutdowns

#### Mounts Easily to Rack

- All-steel unit mounts into 1U of 2- or 4-post rack space
- Mounting hardware included
- 15-ft. (4.57 m) power cord with NEMA 5-15P plug long enough to reach PDU or wall socket

### **Highlights**

- Compatible with devices that charge via AC outlet or USB adapter
- 16 NEMA 5-15R dongles accommodate large transformer plugs
- Heavy-duty steel construction engineered to last
- 15-ft. (4.57 m) AC power cord with NEMA 5-15P input plug
- Ready to mount in 2- or 4-post rack using included hardware

## **Package Includes**

- PS1916D1U 16-Outlet 1U Rack-Mount AC Charger Power Strip
- Mounting hardware
- Owner's Manual





# **Specifications**

| OVERVIEW                           |                                             |
|------------------------------------|---------------------------------------------|
| UPC Code                           | 037332188700                                |
| Product Type                       | Power Strip                                 |
| Charging Form Factor               | Strip                                       |
| Device Compatibility               | Phone; Tablet; Amazon Kindle                |
| INPUT                              |                                             |
| Nominal Input Voltage(s) Supported | 100V AC; 110V AC; 115V AC; 120V AC; 127V AC |
| Input Circuit Breakers             | 15A circuit breaker                         |
| Maximum Input Amps                 | 15                                          |
| Maximum Input Amps Details         | Agency de-rated to 12A continuous           |
| Input Frequency                    | 50 / 60 Hz                                  |
| Input Plug Type                    | NEMA 5-15P                                  |
| Input Cord Length (ft.)            | 15                                          |
| Right-Angle Plug                   | No                                          |
| Input Cord Length (m)              | 4.57                                        |
| Integrated Cord Clip               | No                                          |
| ОИТРИТ                             |                                             |
| Frequency Compatibility            | 50 / 60 Hz                                  |
| Output Receptacles                 | (16) 5-15R                                  |
| Circuit Breaker (amps)             | 15                                          |
| Output Nominal Voltage             | 125V                                        |
| Transformer Accommodation          | (16) Yes                                    |
| Outlet Details                     | 16 NEMA 5-15R dongle output receptacles     |
| Right-Angle Outlets                | Yes                                         |
| CHARGING                           |                                             |
| Number of Charging Ports           | 16                                          |
| Charging Method                    | USB                                         |
| Charging Port Type                 | USB A (FEMALE)                              |
| Charging Ports / Amps              | (16) 12A                                    |
| PHYSICAL                           |                                             |
| Color                              | Black                                       |





| Product Warranty Period (Worldwide) | 2-year limited warranty                                      |
|-------------------------------------|--------------------------------------------------------------|
| WARRANTY & SUPPORT                  |                                                              |
| Product Compliance                  | RoHS; CE (Europe); REACH; FCC (USA)                          |
| Product Certifications              | CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 |
| STANDARDS & COMPLIANCE              |                                                              |
| IP20 Rated                          | No                                                           |
| IP68 Rated                          | No No                                                        |
| Built-In Circuit Breaker            | Yes                                                          |
| Antimicrobial                       | No No                                                        |
| Grounding Details                   | Yes                                                          |
| FEATURES & SPECIFICATIONS           |                                                              |
| Unit Weight (kg)                    | 2.92                                                         |
| Unit Weight (lbs.)                  | 6.44                                                         |
| Unit Dimensions (hwd / cm)          | 4.45 x 48.26 x 10.16                                         |
| Unit Dimensions (hwd / in.)         | 1.750 x 19.000 x 4.000                                       |
| Shipping Weight (kg)                | 3.31                                                         |
| Shipping Weight (lbs.)              | 7.29                                                         |
| Shipping Dimensions (hwd / cm)      | 5.56 x 39.45 x 52.25                                         |
| Shipping Dimensions (hwd / in.)     | 2.19 x 15.53 x 20.57                                         |
| Receptacle Color                    | Black                                                        |
| Mounting Holes or Slots             | No                                                           |
| Power Cord Color                    | Black                                                        |
| Rack Height                         | 1U                                                           |
| Material of Construction            | Metal                                                        |

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.