



Powering Business Worldwide

TRIPP LITE  
SERIES

## Protect It! 7-Outlet Surge Protector, 7 ft. Cord with Right-Angle Plug, 2160 Joules, Diagnostic LEDs, Light Gray Housing

MODEL NUMBER: **SUPER7**



Safeguard your computer, printer, scanner, router, modem and other small home electronics against dangerous surges, spikes and line noise. Recommended for any desktop, network or home application requiring AC line protection.

### Description

Perfect for your home or office workstation, the SUPER7 Protect It!® 7-Outlet Surge Protector features a surge suppression rating of 2160 joules to defend your sensitive electronic components against even the strongest surges and spikes.

Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the SUPER7 protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G). It also filters out electromagnetic interference (EMI) and radio frequency interference (RFI) that can disrupt your electronics and inflict hardware damage or data loss.

Your devices plug into seven NEMA 5-15R outlets. Two outlets are mounted on the side to allow connection of three bulky transformers without blocking adjacent outlets. An integrated 15A circuit breaker protects all outlets and shuts down connected equipment in case of overload. The on/off switch provides one-touch control over connected equipment. Diagnostic LEDs confirm grounding and protection status. The seven-foot (2.1-meter) AC power cord allows the SUPER7 to reach nearby outlets, while its right-angle NEMA 5-15P plug allows furniture and equipment to be placed flush against the wall to save space in your workstation. Keyhole slots incorporated into the bottom panel provide convenient wall or desk mounting options for the light gray plastic housing.

### Features

#### 2160-Joule Surge Protection for Home or Office Electronics

- Protects your computer, printer, scanner, router, modem and other small home electronics against even the strongest surges and spikes
- Recommended for any desktop, network or home electronics application requiring AC line protection
- Full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- Filters out disruptive EMI/RFI line noise that can cause equipment damage or data loss
- Exceeds IEEE 587 Category A and B surge suppression specifications

#### 7 Outlets Accept Wide Range of Electronic Devices

- 7 NEMA 5-15R AC outlets accept most computers and peripherals
- Special side-outlet design accommodates 3 bulky transformers without blocking other outlets

#### Premium Safety Features

- On/off switch provides one-touch control over connected equipment

### Highlights

- 7 NEMA 5-15R outlets, including 3 for bulky transformers
- 2160-joule surge protection rating
- Filters out threatening EMI/RFI line noise
- 15A resettable circuit breaker foils dangerous overloads
- 7 ft. AC power cord with right-angle NEMA 5-15P plug

### Package Includes

- SUPER7 Protect It! 7-Outlet Surge Protector, Light Gray Housing
- Owner's manual



Powering Business Worldwide

TRIPP LITE  
SERIES

- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required
- Diagnostic LEDs confirm grounding and protection status at a glance
- Conforms to current UL 1449 3rd Edition safety standards
- ABS fire retardant plastic case provides extra safety and durability

#### Fits Effortlessly Into Your Workstation

- 7 ft. AC power cord with space-saving right-angle NEMA 5-15P plug allows furniture and equipment to be placed flush against the wall
- Keyhole slots on bottom panel provide convenient wall or desk mounting options

#### Backed by Ultimate Lifetime Insurance

- \$75,000 Ultimate Lifetime Insurance covers any connected components damaged by power surge (U.S., Canada and Puerto Rico only)

## Specifications

| OVERVIEW                           |                                              |
|------------------------------------|----------------------------------------------|
| UPC Code                           | 037332095282                                 |
| INPUT                              |                                              |
| Nominal Input Voltage(s) Supported | 120V AC                                      |
| Recommended Electrical Service     | 120V (110-125V)                              |
| Input Plug Features                | Right Angle (36D)                            |
| Input Cord Gauge Type              | 14 gauge; SJT                                |
| Input Cord Gauge (AWG)             | 14                                           |
| Voltage Compatibility (VAC)        | 120                                          |
| Maximum Surge Amps                 | 144000                                       |
| Input Plug Type                    | NEMA 5-15P                                   |
| Input Cord Details                 | SJT                                          |
| Input Cord Length (ft.)            | 7                                            |
| Right-Angle Plug                   | Yes                                          |
| Input Cord Length (m)              | 2.13                                         |
| Integrated Cord Clip               | No                                           |
| OUTPUT                             |                                              |
| Frequency Compatibility            | 50 / 60 Hz                                   |
| Output Receptacles                 | (7) 5-15R                                    |
| Circuit Breaker (amps)             | 15                                           |
| Transformer Accommodation          | (4) Yes                                      |
| Outlet Orientation                 | Single row of 5, plus 2 side mounted outlets |
| Right-Angle Outlets                | No                                           |



Powering Business Worldwide

TRIPP LITE  
SERIES

| USER INTERFACE, ALERTS & CONTROLS                 |                                                                                           |
|---------------------------------------------------|-------------------------------------------------------------------------------------------|
| Diagnostic LED(s)                                 | Yes                                                                                       |
| Switches                                          | Two position on/off power switch                                                          |
| Diagnostic LED Details                            | Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status |
| SURGE / NOISE SUPPRESSION                         |                                                                                           |
| AC Suppression Joule Rating                       | 2160                                                                                      |
| AC Suppression Response Time                      | < 1 ns                                                                                    |
| Protection Modes                                  | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression              |
| UL1449 Let Through Rating                         | 330 L-G, 400 L-N, 400 N-G                                                                 |
| EMI / RFI Filtering                               | Up to 20 dB                                                                               |
| Automatic Shut-Off                                | Yes                                                                                       |
| DATALINE SURGE SUPPRESSION                        |                                                                                           |
| Cable (Coax) Protection                           | No                                                                                        |
| Network (Ethernet) Protection                     | No                                                                                        |
| Telephone/DSL Protection                          | No                                                                                        |
| PHYSICAL                                          |                                                                                           |
| Material of Construction                          | Plastic                                                                                   |
| Power Cord Color                                  | Light Gray                                                                                |
| Housing Color                                     | Light Gray                                                                                |
| Mounting Holes or Slots                           | Yes                                                                                       |
| Slot or Hole Mount Measurement (Center to Center) | Distance between slots = 70 mm; Distance between slot height = 24 mm                      |
| Outlets Measurement (Center to Center)            | Between Standard Outlets = 29mm; Between Transformer Outlets = 48mm                       |
| Receptacle Color                                  | Light gray                                                                                |
| Shipping Dimensions (hwd / in.)                   | 12.60 x 1.90 x 5.90                                                                       |
| Shipping Dimensions (hwd / cm)                    | 32.00 x 4.83 x 14.99                                                                      |
| Shipping Weight (lbs.)                            | 1.55                                                                                      |
| Shipping Weight (kg)                              | 0.70                                                                                      |
| Unit Dimensions (hwd / in.)                       | 1.540 x 2.720 x 10.300                                                                    |
| Unit Dimensions (hwd / cm)                        | 3.91 x 6.91 x 26.16                                                                       |
| Unit Weight (lbs.)                                | 1.39                                                                                      |
| Unit Weight (kg)                                  | 0.63                                                                                      |
| Input Cord Color                                  | Gray                                                                                      |



Powering Business Worldwide

TRIPP LITE  
SERIES

| FEATURES & SPECIFICATIONS                                  |                                                                                                                         |
|------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Rotatable Outlets                                          | No                                                                                                                      |
| Antimicrobial                                              | No                                                                                                                      |
| STANDARDS & COMPLIANCE                                     |                                                                                                                         |
| Product Certifications                                     | CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed |
| Product Compliance                                         | RoHS                                                                                                                    |
| WARRANTY & SUPPORT                                         |                                                                                                                         |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty                                                                                               |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$75,000 <a class="insuranceLink" href="//tripplite.eaton.com/support/insurance-policy">Ultimate Lifetime Insurance</a> |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.