

# Power Cord, NEMA 5-15P to Right-Angle C15 - Heavy-Duty, 15A, 125V, 14 AWG, 8 ft. (2.43 m), Black

MODEL NUMBER: P019-008-C15RA



C15 right-angle power cable connects a PoE network switch or other device with a C16 power inlet in tight spaces or awkward angles.

## Features

**IEC C15 Power Cord for Network Devices That Require a Heavy-Gauge Connection** This IEC C15 power cable features 14 AWG wire suitable for high power connections, making it reliable for large server applications that require a higher-rated, heavier-gauge cable. The C15 connector is designed for higher-temperature devices, such as electric kettles, PoE (Power over Ethernet) switches with high-wattage power supplies, and similar network components. This cord can also replace or upgrade the standard power cord provided by the device's manufacturer. The 8-ft. (2.43 m) length allows you flexibility in placing equipment with respect to the power outlet.

**Right-Angle C15 Plug Makes Connecting in Tight Spaces Easier** The C15 right-angle power cable is easier to install in confined spaces, such as the back of a rack enclosure cabinet. When plugged in, the right-angled C15 plug guides the cable parallel to your peripheral, allowing you to push the device up against a wall or hide it behind a desk to maximize space.

## Highlights

- Right-angle C15 plug allows easier connection in confined or hard-to-reach spaces
- Recommended for powering PoE switches with high-wattage power supplies
- 8-ft. (2.43 m) length allows flexibility in placing devices in relationship to AC outlet
- NEMA 5-15P to C15 cable replaces or upgrades original manufacturer's power cord
- Thick 14 AWG wire gauge manages high power levels required for larger equipment

## Applications

- Connect devices like high-wattage PoE switches to a PDU up to 8-ft. (2.43 m) away in your data center
- Extend an existing power connection up to 8-ft. (2.43 m) to more easily place a device or reach a power source
- Update or replace the standard power cord provided by a device's original manufacturer
- Power a device located in a hard-to-access area behind a desk or flush against a wall

## Package Includes

- P019-008-C15RA 5-15P to Right-Angle C15 Power Cord, 8-ft. (2.43 m), Black

## Specifications

| OVERVIEW                    |                                            |
|-----------------------------|--------------------------------------------|
| UPC Code                    | 037332202413                               |
| Device Compatibility        | Computer; Server; Network Switch; UPS; PDU |
| Country/Region              | North America                              |
| INPUT                       |                                            |
| Maximum Input Amps          | 15                                         |
| Voltage Compatibility (VAC) | 125                                        |



Powering Business Worldwide

TRIPP LITE  
SERIES

| CONNECTIONS                        |                             |
|------------------------------------|-----------------------------|
| Side A - Connector 1               | NEMA 5-15P                  |
| Side B - Connector 1               | IEC-320-C15 – RIGHT ANGLE   |
| PHYSICAL                           |                             |
| Plug Color                         | Black                       |
| Cable Jacket Color                 | Black                       |
| Cable Jacket Material              | PVC                         |
| Cable Jacket Rating                | VW-1                        |
| Power Cord Jacket Type             | SJT                         |
| Cable Outer Diameter (OD)          | 9.2mm                       |
| Number of Conductors               | 3                           |
| Wire Gauge (AWG)                   | 14                          |
| Wire Gauge (OD - mm <sup>2</sup> ) | 2.08                        |
| Cable Length (ft.)                 | 8                           |
| Cable Length (m)                   | 2.44                        |
| Shipping Dimensions (hwd / in.)    | 0.50 x 11.80 x 14.00        |
| Shipping Dimensions (hwd / cm)     | 1.27 x 29.97 x 35.56        |
| Shipping Weight (lbs.)             | 1.00                        |
| Shipping Weight (kg)               | 0.45                        |
| ENVIRONMENTAL                      |                             |
| Operating Temperature Range        | -4° to 140°F (-20° to 60°C) |
| Storage Temperature Range          | -4° to 140°F (-20° to 60°C) |
| Operating Humidity Range           | 10% to 65% RH               |
| Storage Humidity Range             | 10% to 65% RH               |
| FEATURES & SPECIFICATIONS          |                             |
| Antibacterial                      | No                          |
| Angled Plug                        | Yes                         |
| High Voltage                       | No                          |
| Locking Plug                       | No                          |
| Coiled Power Cord                  | No                          |
| STANDARDS & COMPLIANCE             |                             |
| Product Certifications             | cUL Listed; UL Listed       |
| Product Compliance                 | RoHS                        |

WARRANTY & SUPPORT

|                                        |                           |
|----------------------------------------|---------------------------|
| Product Warranty Period<br>(Worldwide) | Lifetime limited warranty |
|----------------------------------------|---------------------------|

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.