**Important Note**

This product is not available in the European Union. If you live in one of these countries, please contact us for further assistance.

# Power Extension Cord, Locking C19 to C20 - Heavy-Duty, 20A, 100-250V, 12 AWG, 10 ft. (3.05 m), Black

MODEL NUMBER: **P036-L10**



C20 to C19 cord powers a server, router, switch, blade server enclosure or other network device that requires a heavy-gauge cable.

## Features

**C20 to C19 Power Cable for Network Devices That Require a Heavy-Gauge Connection**This rugged cord features 12 AWG wire suitable for high power connections, making it a reliable solution for large server applications that require a higher-rated, heavier-gauge cable. It can be used to connect a server, router, switch, blade server enclosure or other network device to a UPS system or PDU. It is also an ideal replacement or upgrade from the standard power cord provided by the device's manufacturer. The 10-ft. (3.05 m) length allows you great flexibility in placing equipment with respect to the power outlet.

**Locking C19 Connector Helps Prevent Accidental Disconnection and Expensive Downtime**Having a cable come loose accidentally can mean the loss of power and costly downtime. The locking C19 connector helps you avoid such danger, protecting critical equipment by maintaining a secure link without failure. The locking cable is also invaluable when moving equipment in a rack or removing equipment from tight areas, ensuring the power cord always stays connected.

**Lifetime Warranty**The P036-L10 is backed by a lifetime warranty, ensuring reliability and performance.

## Highlights

- Recommended for powering network devices that require heavy-gauge cabling
- 10-ft. (3.05 m) length allows great flexibility in placing devices in relationship to AC outlet
- Reliable replacement or upgrade from standard power cord provided by manufacturer
- Thick 12 AWG wire gauge manages high power levels required for larger equipment
- Locking C19 connector maintains secure link to avoid loss of power and costly downtime

## Applications

- Connect devices like servers, routers and network switches to a UPS system up to 10-ft. (3.05 m) away in your data center
- Extend an existing power connection up to 10-ft. (3.05 m) to more easily place a device or reach a power source in a rack
- Update or replace the standard power cord provided by a device's original manufacturer

## Package Includes

- P036-L10 C20 to C19 Power Cable, Locking C19 Connector, 10-ft. (3.05 m), Black

# Specifications

| OVERVIEW | |
|---|---|
| UPC Code | 037332218322 |
| Device Compatibility | Server; Router; Network Switch; UPS; PDU |
| Country/Region | North America |

| INPUT | |
|---|---|
| Maximum Input Amps | 20 |
| Voltage Compatibility (VAC) | 100-250 |

| CONNECTIONS | |
|---|---|
| Side A - Connector 1 | IEC-320-C20 |
| Side B - Connector 1 | IEC-320-C19 - LOCKING |

| PHYSICAL | |
|---|---|
| Plug Color | Black |
| Cable Jacket Color | Black |
| Cable Jacket Material | PVC |
| Cable Jacket Rating | VW-1 |
| Power Cord Jacket Type | SJT |
| Cable Outer Diameter (OD) | 10.8mm |
| Number of Conductors | 3 |
| Wire Gauge (AWG) | 12 |
| Wire Gauge (OD - mm²) | 3.31 |
| Cable Length (ft.) | 10 |
| Cable Length (m) | 3.05 |
| Shipping Dimensions (hwd / in.) | 12.80 x 8.59 x 0.50 |
| Shipping Dimensions (hwd / cm) | 32.51 x 21.82 x 1.27 |
| Shipping Weight (lbs.) | 1.51 |
| Shipping Weight (kg) | 0.68 |
| Unit Dimensions (hwd / in.) | 0.000 x 0.000 x 0.000 |

| ENVIRONMENTAL | |
|---|---|
| Operating Temperature Range | -4° to 221°F (-20° to 105°C) |
| Storage Temperature Range | -4° to 221°F (-20° to 105°C) |
| Operating Humidity Range | 0% to 65% RH |
| Storage Humidity Range | 0% to 65% RH |

| FEATURES & SPECIFICATIONS | |
|---|---|
| Antibacterial | No |
| Angled Plug | No |
| High Voltage | Yes |
| Locking Plug | Yes |

| Coiled Power Cord | No |
|---|---|
| **STANDARDS & COMPLIANCE** | |
| Product Certifications | CSA (Canada); cUL Listed; UL Listed |
| Product Compliance | RoHS; REACH |
| **WARRANTY & SUPPORT** | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

1000 Eaton Boulevard

Cleveland, OH 44122

United States

https://tripplite.eaton.com