


FBNAB3100ZF110

Aliases (BNAB3100ZF110)

KEMET, FBN, EMI/RFI Filters, Noise Suppression, 250 VAC, 6 A, 55x51x24mm



Click here for the 3D model.

Dimensions	
L	55mm NOM
W	51mm NOM
Н	23.5mm NOM

Packaging Specifications	
Packaging	Bulk
Packaging Quantity	1

General Information		
Series	FBN	
Style	Chassis Mount	
Description	Compact, Lightweight with metalic enclosure	
Features	Compact, lightweight	
RoHS	Yes	
Qualifications	IEC/EN 60939, UL, CSA	
Terminal Type	Faston	

Specifications	
Voltage AC	250 VAC
Rated Frequency	50-60 Hz
Rated Current	6 A
Rated Temperature	40°C
Temperature Range	-25/+85°C
Climate Category	25/085/21
Test Voltage DC (P to P)	1700 VDC
Test Voltage DC (P to E)	3000 VDC
Leakage Current	0.21 mA (MAX)
ESR	1mOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.