



Relays & Contactors > Relays > Power Relays > Power Relay, 75A, Standard, Monostable, DC



Relay Type: **Standard**

Coil Magnetic System: **Monostable**

Coil Resistance: **76 Ω**

Coil Special Features: **Coil Suppression Diode**

Coil Voltage Rating: **18 VDC, 32 VDC**

[All Power Relay, 75A, Standard, Monostable, DC \(19\)](#)

Features

Product Type Features

Relay Type	Standard
------------	----------

Configuration Features

Coil Special Features	Coil Suppression Diode
Contact Arrangement	1 Form X (SPST-NO-DM)
Contact Number of Poles	1

Electrical Characteristics

Coil Resistance	76 Ω
Coil Voltage Rating	18 VDC, 32 VDC
Contact Current Rating	75 A
Contact Voltage Rating	28 VDC

Contact Features

Contact Material	AgSnO2
------------------	--------

Termination Features

Relay Connection Type	Terminals
Terminal Configuration	Screw Terminals



Mechanical Attachment

Product Mounting Feature Type	Mounting Brackets
Product Mount Type	Chassis

Dimensions

Product Width	62 mm[2.44 in]
Product Length	82.5 mm[3.24 in]
Product Height	50 mm[1.96 in]

Operation/Application

Actuating System	DC
Coil Magnetic System	Monostable

Other

Contact Current Class	75 A
-----------------------	------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Pb (92.5% in Component part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides

on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # CAT-AL6-KSPR2975
Power Relay, 75A, Standard, Monostable, DC

Also in the Series | KISSLING Series 29



Power Relays(122)

Customers Also Bought



TE Part # 812836-000
222K121-3-0




TE Part # 1-332070-1
SOCKET,MIN-SPR AU SER-4



TE Part # K1021599
Relay 29-221-12



TE Part # 1-1393203-1
V23148-A0007-A101



TE Part # 2-2176483-6
RA73F 2A 1K0 0.1% 5K RL



TE Part # 7574442007
RAYRIM-NR8-0-STK



TE Part # K1008699
Relay 26-60-05



TE Part # K1012918
Relay 26-70-04

Documents

Product Drawings



Relay 29-011-12A

German

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_29-011-12A_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_29-011-12A_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_29-011-12A_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[KISSLING SINGLE POLE POWER RELAYS Series 29 / 75A](#)

English