

2909916

https://www.phoenixcontact.com/us/products/2909916

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

PLC logic starter kit 3, consisting of: plug-in stand-alone logic module (SAM 2), eight relay output terminal blocks with Push-in connection (250 V AC/DC, max. 6 A), and micro USB programming coble



Commercial data

Item number	2909916
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C424
Product key	CK26Z2
Catalog page	Page 434 (C-5-2019)
GTIN	4055626409122
Weight per piece (including packing)	612.7 g
Weight per piece (excluding packing)	600 g
Customs tariff number	85371098
Country of origin	DE



2909916

https://www.phoenixcontact.com/us/products/2909916

Set consists of

PLC-V8C/PT-24DC/SAM2 - Controller

2907443

https://www.phoenixcontact.com/us/products/2907443



PLC logic stand-alone module, Generation 2, with 16 I/Os, for plug-in connection to eight digital or analog PLC-INTERFACE terminal blocks, cannot be extended, real-time clock, micro USB female connector, accommodates memory module and Bluetooth adapter, Push-in connection

PLC-RPT- 24DC/ 1/ACT - Relay Module

2900312

https://www.phoenixcontact.com/us/products/2900312



PLC-INTERFACE for output functions, consisting of PLC-BPT.../ACT basic terminal block with push-in connection and plug-in miniature relay with power contact, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input voltage 24 V DC



2909916

https://www.phoenixcontact.com/us/products/2909916

CAB-USB A/MICRO USB B/2,0M - Connecting cable

2701626

https://www.phoenixcontact.com/us/products/2701626



Connecting cable, for connecting the controller to a PC for PC Worx and LOGIC+, USB A to micro USB B, 2 m in length.



2909916

https://www.phoenixcontact.com/us/products/2909916

Technical data

Notes on operation	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
Product properties	
Product type	Starter kit
Mounting	
Mounting type	DIN rail mounting



2909916

https://www.phoenixcontact.com/us/products/2909916

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/2909916



EAC

Approval ID: RU C-DE.A*30.B.01082



2909916

https://www.phoenixcontact.com/us/products/2909916

Classifications

ECLASS

202.00				
	ECLASS-11.0	27242219		
	ECLASS-12.0	27242219		
	ECLASS-13.0	27242219		
ETIM				
	ETIM 9.0	EC002581		
U	NSPSC			
	UNSPSC 21.0	32151700		



2909916

https://www.phoenixcontact.com/us/products/2909916

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-l
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Hexahydromethylphthalic anhydride(CAS: n/a)
	Lead(CAS: 7439-92-1)
SCIP	3b9d33fc-f967-4da8-973b-5c3ee2997769

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com