HellermannTyton

Specification Sheet

Part Number: 169-60129

Excellent flame-resistant properties with higher operating temperature ranges for a wider range of application environments.

High-visibility orange color offers safe identification of high-voltage cabling.

Lateral slit allows for fast and easy insertion, inspection and future access to cabling.

The UV additive prevents damage and discoloration caused by long-term exposure to sunlight.



Article Number 169-60129

Type CTPPFRUV10

Color Orange (OG), High Voltage (HV)

Quantity Per carton

Product Description

HellermannTyton's Orange Flame-Retardant Polypropylene with UV Inhibitor Convoluted Slit Tubing provides high visibility, is self-extinguishing and offers elevated protection against UV radiation for long-term outdoor use. Convoluted tubing efficiently protects wire harness assemblies, hoses and cables against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires while reducing the chance of installation damage. Its unique blend of flame-retardant polypropylene is suitable for applications requiring self-extinguishing materials and complies with UL 94 V-2 standards.

Short Description	Convoluted Tubing, Slit, 1.0" Dia, PP-FR-UV, Orange, 300 ft/carton	
Global Part Name	CTPPFRUV10-PPFRUV-OG	
Inner Diameter D (Imperial)	1.069	
Inner Diameter D (Metric)	27.16	
Diameter D (Imperial)	1.304	
Diameter D (Metric)	33.13	
Outside Diameter OD (Imperial)	1.304	
Outside Diameter OD (Metric)	33.13	
Nominal Diameter (Imperial)	1	
Nominal Diameter (Metric)	25.4	
Wall Thickness WT (Imperial)	0.006	
Wall Thickness WT (Metric)	0.152	
Material	Polypropylene, flame retardant, UV-stabilized (PPFRUV)	

PPFRUV

UL 94 V-2

Material Shortcut

Flammability

Halogen Free	No
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +257°F (-40°C to +125°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	300
Package Quantity (Metric)	91.44
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions