




Switches > Push Button Switches



Configuration (Pole-Throw): **Single Pole - Single Throw**
Push Button Switch Product Type: **General Purpose Push Button Switch**
Number of Actuators: **Single**
Actuator Profile: **Flush**
Bushing Style: **Threaded**

Features

Product Type Features

Push Button Switch Product Type	General Purpose Push Button Switch
Illuminated	With
Actuator Style	Round

Configuration Features

Configuration (Pole-Throw)	Single Pole - Single Throw
Number of Actuators	Single
Snap Action	Without
Support Bracket	Without
Switch Feedback Type	Auditory
Operating Function	Momentary

Electrical Characteristics

Contact Current Rating	.12 A
Operating Voltage Range	32 VAC, 125 VAC

Body Features



Actuator Force	306 - 612 g[10.8 - 21.6 oz]
Case Material	Diallyl Phthalate (DAP)
Actuator Material	Polyamide
Product Orientation	Vertical
Actuator Profile	Flush
Bushing Style	Threaded
Bushing Thread Size	M12 x .75
Actuator Color	Black

Contact Features

Switch Contact Plating Material	Gold over Silver
---------------------------------	------------------

Housing Features

Process Sealed	Yes
----------------	-----

Industry Standards

IP Rating	IP68
-----------	------

Packaging Features

Packaging Method	Loose Piece
------------------	-------------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: Pb (4% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2329387-4

PB OFF/ON FC BLK M1 TERM GRE LED IP68

TE Part # 2329383-3

PB OFF/ON FC YLW M1 TERM. IP68

TE Part # 2329359-1

PN OFF/ON HC BLK M1 TERM IP68 500MM LHS

TE Part # 2329359-2

PN OFF/ON HC RED M1 TERM IP68 500MM LHS

TE Part # 2329361-3

PB OFF/ON RC YLW M1 TERM IP68 500MM L

Also in the Series | Alcoswitch PB6

Push Button Switches(165)

Customers Also Bought





TE Part # 0413-217-1605
SEALING PLUG, SIZE 16, LOCKING, WHT



TE Part # 1546413-3
ETHERNET RJ-45 BLKHD PASSTHRU



TE Part # 1658527-5
622-1430LF FEM SOCKT,LEAD FREE



TE Part # 2301838-2
AMPL REC HD20, VERT, 9P, B/L,4-40 S /LOCK



TE Part # 2329387-3
PB OFF/ON FC BLK M1 TERM YLW LED IP68



TE Part # 2329387-4
PB OFF/ON FC BLK M1 TERM GRE LED IP68



TE Part # 2329389-4
PB OFF/ON FC BLK M1 TERM GRE LED IP68 50



TE Part # 2329387-6
PB OFF/ON FC RED M1 TERM WHI LED IP68



TE Part # DT04-4P-L012
REC, 4P, GRY, N, FLANGE



TE Part # 175444-9
HYBRID I/O CAP ASSY 34P

Documents

Product Drawings

PB OFF/ON FC BLK M1 TERM BLU LED IP68

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2329387-5_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2329387-5_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2329387-5_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



IP68 Sub Mini PB Data Sheet

English