



**Product:** [Consolidation Enclosures](#)

## Belden Consolidation/MDU Enclosures

### Product Description

Consolidation/MDU Enclosures: In-Suite Distribution Target Markets: Hospitality & Dwelling; Public Venue

### Technical Specifications

#### Application

Product Overview:	Designed to house connectivity and provide cable routing options. Knockouts located in the bottom are designed to accommodate single or full-width AC power modules, mini and universal DC power supplies. Enclosure is capable of housing different types of ONTs.
Environmental Space:	Indoor

#### Construction and Dimensions

Construction:	Steel
Width:	14.38 in

#### Mechanical Characteristics

Mounting:	Vertical
-----------	----------

#### Environmental and Overall Characteristics

Finish:	Medium Texture Powder Coat Finish
Material:	Steel
Color:	White

#### Related Part Numbers

Packaging:	Individually packaged in a cardboard box
------------	--

#### Variants

Item #	Height	Width	Depth	Door Type
XRES1414	14.0 in	14.38 in	3.63 in	Enclosure - No Door
XRES1414FC	14.0 in	15.8 in		Screw on Flush Cover
XRES1414VHD	14.0 in	15.8 in		Vented Hinged Cover
XRES2114	21.0 in	14.38 in	3.63 in	Enclosure - No Door
XRES2114FC	21.0 in	15.8 in		Screw on Flush Cover
XRES2114VHD	21.0 in	15.8 in		Vented Hinged Cover
XRES2814	28.0 in	14.38 in	3.63 in	Enclosure - No Door
XRES2814FC	28.0 in	15.8 in		Screw on Flush Cover
XRES2814VHD	28.0 in	15.8 in		Vented Hinged Cover
XRES4214	42.0 in	14.38 in	3.63 in	Enclosure - No Door
XRES4214VHD	42.0 in	15.8 in		Vented Hinged Cover
XRES4214FC	42.0 in	15.8 in		Screw on Flush Cover

Update and Revision:	Revision Number: 0.216 Revision Date: 11-09-2022
----------------------	--

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.