Specifications



Spacial SF/SM partial 19" swing rack - 601 mm

NSYRSWP12

Main

RangeSpacialAccessory / Separate Part CategoryMounting accessoryProduct Or Component Type19" rackApplicationElectronic applicationFor Enclosure Nominal Dimensions- H: 601 mmRack TypePartial swingMounting LocationFront of enclosureMounting SupportPartial 19" swing rack supportRange CompatibilitySpacial Spacial SF Spacial Spacial SMDevice Composition1 rackNumber Of Units 19"12	
Category 19" rack Product Or Component Type 19" rack Application Electronic application For Enclosure Nominal - H: 601 mm Dimensions Partial swing Mounting Location Front of enclosure Mounting Support Partial 19" swing rack support Range Compatibility Spacial Spacial SF Spacial Spacial SM Device Composition 1 rack	
Application Electronic application For Enclosure Nominal Dimensions - H: 601 mm Rack Type Partial swing Mounting Location Front of enclosure Mounting Support Partial 19" swing rack support Range Compatibility Spacial Spacial SF Spacial Spacial SM Device Composition 1 rack	
For Enclosure Nominal Dimensions - H: 601 mm Rack Type Partial swing Mounting Location Front of enclosure Mounting Support Partial 19" swing rack support Range Compatibility Spacial Spacial SF Spacial Spacial SM Device Composition 1 rack	
Dimensions International Rack Type Partial swing Mounting Location Front of enclosure Mounting Support Partial 19" swing rack support Range Compatibility Spacial Spacial SF Spacial Spacial SM Device Composition 1 rack	
Mounting Location Front of enclosure Mounting Support Partial 19" swing rack support Range Compatibility Spacial Spacial SF Spacial Spacial SM Device Composition 1 rack	
Mounting Support Partial 19" swing rack support Range Compatibility Spacial Spacial SF Spacial Spacial SM Device Composition 1 rack	
Range Compatibility Spacial Spacial SF Spacial Spacial SM Device Composition 1 rack	
Spacial Spacial SM Device Composition 1 rack	
Number Of Units 19" 12	
·	

Complementary

Material	Steel
Enclosure/Cubicle Description	Floor-standing enclosure
Surface Finish	Zinc coated
Lock Type	Lock 5 mm double bar
Fixing Mode	By fixing element
Adjustment	Adjustable in depth every 25 mm
Permanent Permissible Load	2 kg per unit
Opening Of The 19" Racks	Reversible 120 °
Height	601 mm
Width	600 mm
Depth	601 mm

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.5 cm
Package 1 Width	51.5 cm
Package 1 Length	61.5 cm

Package 1 Weight	3.44 kg
Unit Type Of Package 2	РАМ
Number Of Units In Package 2	20
Package 2 Height	105.0 cm
Package 2 Width	100.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	82.0 kg

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance



Eq

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations