

Part Number: 2240861044

Product Description: Mini-Fit Max Female-to-Pigtail Off-the-Shelf (OTS) Cable Assembly, Tin(Sn) Plating, 4 Circuits, 600.00mm Length,

2.5mm<sup>2</sup> Wire, Black

Status: Active

Series Number: 224086

**Product Category:** Power and Signal Cable

**Assemblies** 

#### **Documents & Resources**

### **Drawings**

Drawing 2240861044\_sd.pdf

## **Product Environment Compliance**

### Compliance

| GADSL/IMDS         | Not Relevant                                      |
|--------------------|---|
| China RoHS         | <b>©</b>  |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-<br>21            |
| REACH SVHC         | Not Contained per D(2023)8585-DC<br>(23 Jan 2024) |
| EU RoHS            | Compliant per EU 2015/863                         |

## Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## **EU RoHS Certificate of Compliance**

#### **Part Details**

# General

| Status                 | Active   |
|------------------------|--|
| Category               | Power and Signal Cable Assemblies  |
| Series                 | 224086   |
| Description            | Mini-Fit Max Female-to-Pigtail Off-<br>the-Shelf (OTS) Cable Assembly,<br>Tin(Sn) Plating, 4 Circuits,<br>600.00mm Length, 2.5mm <sup>2</sup> Wire,<br>Black |
| Application            | Power, Wire-to-Board, Wire-to-Wire   |
| Assembly Configuration | Single Ended Connector   |
| Connector to Connector | Mini-Fit Max-to-Pigtail  |
| Product Family         | Mini-Fit Family Power Connectors   |
| Product Name           | Mini-Fit Max   |
| Туре                   | Discrete Wire Assembly   |
| UPC                    | 196823397264   |

# Electrical

| Current - Maximum per Contact | 20A           |
|-------------------------------|---------------|
| Voltage - Maximum             | 600V AC (RMS) |

# Physical

| Cable Length                   | 600.00mm                 |
|--------------------------------|--------------------------|
| Circuits (Loaded)              | 4                        |
| Circuits (maximum)             | 4                        |
| Color - Resin                  | Black                    |
| Gender                         | Female-Pigtail           |
| Lock to Mating Part            | Yes                      |
| Material - Metal               | High Conductivity Copper |
| Material - Plating Mating      | Tin                      |
| Material - Plating Termination | Tin                      |
| Material - Resin               | Nylon                    |
| Net Weight                     | 58.426/g                 |
| Number of Rows                 | 2                        |
| Overmolded                     | No                       |
| Packaging Type                 | Bag                      |

| Pitch - Mating Interface    | 4.20mm               |
|-----------------------------|----------------------|
| Plating min - Mating        | 1.020µm              |
| Plating min - Termination   | 2.540µm              |
| Single Ended                | Yes                  |
| Termination Interface Style | Crimp or Compression |
| Wire/Cable Type             | UL 11028             |
| Wire Insulation Diameter    | 2.65mm               |
| Wire Size (AWG)             | 14                   |

# Mates With / Use With

# Mates with Part(s)

| Description                               | Part Number |
|---|-------------|
| Mini-Fit Max Vertical Dual Row<br>Headers | 212520      |

This document was generated on Apr 08, 2024