### Power Versa-Lock | Power Versa-Lock 5.0

TE Internal #: 2325347-4


Interface Seal, Silicone Rubber, Blue, 4 Position, -30 - 105 °C [-22 -

221 °F] Operating Temperature, Power Versa-Lock 5.0

View on TE.com >



Connectors > Connector Accessories > Connector Seals & Cavity Plugs



Connector Seal & Plug Type: Interface Seal
Primary Product Material: Silicone Rubber

Primary Product Color: Blue

Operating Temperature (Max): 105 °C [221 °F]

Number of Positions: 4

### **Features**

# Product Type Features

Connector Seal & Plug Type	Interface Seal
Configuration Features	
Number of Positions	4
Body Features	
Primary Product Material	Silicone Rubber
Primary Product Color	Blue
Usage Conditions	
Usage Conditions  Operating Temperature (Max)	105 °C[221 °F]
	105 °C[221 °F] -30 - 105 °C[-22 - 221 °F]
Operating Temperature (Max)	
Operating Temperature (Max) Operating Temperature Range	

# **Product Compliance**



#### For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240)  Candidate List Declared Against: JAN 2024 (240)  SVHC > Threshold:  Octamethylcyclotetrasiloxane (D4) (.5% in Component Part)  Dodecamethylcyclohexasiloxane (D6) (.5% in Component Part)  Decamethylcyclopentasiloxane (D5) (.5% in Component Part)  Article Safe Usage Statements:  Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

# **Compatible Parts**





TE Part # 1-2381315-3
Power Versa-Lock PLUG, 1X3 KEY A,
GWT



TE Part # 1-2381315-4
Power Versa-Lock PLUG, 1X4 KEY A,
GWT





# Also in the Series | Power Versa-Lock 5.0





Connector Contacts(12



Connector Hardware(5)



Connector Seals & Cavity Plugs(9)



Insertion & Extraction Tools(2)



Rectangular Power Connectors(77)

### **Documents**

### **Product Drawings**

POWER VERSA-LOCK, INTERFACE SEAL, 1X4

English

#### **CAD Files**

Customer View Model ENG\_CVM\_CVM\_2325347-4\_A.3d\_stp.zip

English



**Customer View Model** 

ENG\_CVM\_CVM\_2325347-4\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2325347-4\_A.3d\_igs.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

**Product Specifications** 

**Application Specification** 

English

**Instruction Sheets** 

Instruction Sheet (U.S.)

English