# 1-292254-0 ACTIVE

#### **AMP CT**

TE Internal #: 1-292254-0

Connector Assembly, Plug to Plug Relay Header, Wire-to-Panel, 10

Position, .078 in [2 mm] Centerline, 1 Row, Natural, Mating

Retention, Signal, AMP CT

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings











Connector Product Type: Connector Assembly

Connector & Housing Type: Plug to Plug Relay Header

Connector System: Wire-to-Panel

Number of Positions: 10

Centerline (Pitch): 2 mm [.078 in]

Contact Retention Within Housing

#### **Features**

#### **Product Type Features**

| Connector Product Type     | Connector Assembly        |
|----------------------------|---------------------------|
| Connector & Housing Type   | Plug to Plug Relay Header |
| Connector System           | Wire-to-Panel             |
| Sealable                   | No                        |
| Configuration Features     |                           |
| Number of Positions        | 10                        |
| Number of Rows             | 1                         |
| Electrical Characteristics |                           |
| Operating Voltage          | 125 V                     |
| Body Features              |                           |
| Primary Product Color      | Natural                   |
| Contact Features           |                           |

Without



| Contact Type                                | Pin                          |
|---|------------------------------|
| Contact Base Material                       | Brass                        |
| Contact Current Rating (Max)                | 4 A                          |
| Mechanical Attachment                       |                              |
| Strain Relief                               | Without                      |
| Panel Mount Feature                         | With                         |
| Panel Mount Feature Type                    | Latches                      |
| Mating Retention Type                       | Locking Latch                |
| Mating Retention                            | With                         |
| Connector Mounting Type                     | Panel Mount                  |
| Housing Features                            |                              |
| Housing Material                            | Nylon 66                     |
| Centerline (Pitch)                          | 2 mm[.078 in]                |
| Dimensions                                  |                              |
| Connector Length                            | 23.78 mm[.936 in]            |
| Panel Thickness (Recommended)               | .81 – 1.6 mm[.032 – .063 in] |
| Connector Height                            | 12 mm[.472 in]               |
| Connector Width                             | 6 mm[.236 in]                |
| Usage Conditions                            |                              |
| Operating Temperature Range                 | -40 – 105 °C[-40 – 221 °F]   |
| Operation/Application                       |                              |
| Circuit Application                         | Signal                       |
| Industry Standards                          |                              |
| Compatible With Agency/Standards Products   | CSA, UL                      |
| Compatible With Approved Standards Products | UL Recognized                |
| UL Flammability Rating                      | UL 94V-0                     |
| Packaging Features                          |                              |
| Packaging Quantity                          | 300                          |
| Packaging Method                            | Bag & Box                    |

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>



| EU RoHS Directive 2011/65/EU                  | Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per<br>homogenous material. Also BFR/CFR/PVC<br>Free                               |
| Solder Process Capability                     | Not applicable for solder process capability  |

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts








### Also in the Series | AMP CT





Connector Contacts(8)



Connector Hardware(46)



PCB Headers & Receptacles(756)



Wire-to-Board Connector Assemblies & Housings(255)

# Customers Also Bought



TE Part #1-292215-6 MINI CT SGL RELAY 16P NAT



TE Part #2-353294-8 AMP MINI D/R HDR HSG 28P NATU



TE Part #292215-9 MINI CT SGL RELAY 9P NAT



TE Part #3-353293-1
1.5MM CT MT REC ASSY 11P BLACK



TE Part #3-353293-5
1.5MM CT MT REC ASSY 15P BLACK



TE Part #3-353293-3
1.5MM CT MT REC ASSY 13P BLACK



TE Part #3-353293-0 1.5MM CT MT REC ASSY 10P BLACK





TE Part #8-292112-2 MT REC ASSY (#26,28)

### **Documents**

**Product Drawings** 

CT RELAY HDR ASSY 10P NAT

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1-292254-0\_D.2d\_dxf.zip



English

**Customer View Model** 

ENG\_CVM\_CVM\_1-292254-0\_D.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-292254-0\_D.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### **Product Specifications**

AMP COMMON TERMINATION (CT), CONNECTOR, 2mm PITCH, M/T TYPE, LEAD FREE VERSION

Japanese

**Product Specification** 

Japanese