

Part Number : 643191211

Series Number : 64319 Product Category : Connector Housings

Documents & Resources

Drawings Drawing 643191211_sd.pdf

3D Models and Design Files

3D Model 643191211_stp.zip

Specifications

Application Specification AS-64319-002-001.pdf Application Specification AS-64319-002-CH-001.pdf Application Specification AS-64319-002-FR-001.pdf Application Specification AS-64319-002-SP-001.pdf Application Specification 984200002-AS-KR-000.pdf Application Specification AS-98420-002-001.pdf Application Specification AS-98420-002-CH-001.pdf Application Specification AS-98420-002-FR-001.pdf Application Specification AS-98420-002-FR-001.pdf Application Specification AS-98420-002-FR-001.pdf Packaging Specification PK-64319-001-001.pdf Product Specification PS-64319-002-001.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant
China RoHS	®
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Not Low-Halogen per IEC 61249-2- 21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

Product Description : .635mm, 1.50mm, CMC Receptacle, 32 Circuits, Left Wire Output, Black Coding, Mat Sealed Status : Active

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Connector Housings
Series	64319
Description	.635mm, 1.50mm, CMC Receptacle, 32 Circuits, Left Wire Output, Black Coding, Mat Sealed
Application	Automotive, Power, Wire-to-Board
Comments	Current tested on a 5 terminals loaded connector, current for temperature increase of 40°C; Current max = 6.0A for 0.635mm Terminal (0.75mm ² wire) and 12.0A for 1.50mm Terminal (2.00mm ² wire)
More Detailed Tech Information	Sealed, high-density, modular connecting system for Power Train and Body Electronics applications in cars, trucks, busses
Product Family	CMC and CMX Sealed, Hybrid, Modular Connectors
Product Name	СМС
UPC	883906129736

Physical

Circuits Detail	8 x 1.5mm & 24 x 0.635mm terminals
Circuits (maximum)	32
Color - Resin	Black

Gender	Receptacle
Glow-Wire Capable	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Resin	Polyester
Net Weight	29.426/g
Number of Rows	4
Packaging Type	Carton
Panel Mount	No
Pitch - Mating Interface	2.54mm, 3.70mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40° to +125°C

Solder Process Data

Lead-Free Process Capability N/A	ead-Free Process Capability	N/A
----------------------------------	-----------------------------	-----

Mates With / Use With

Mates with Part(s)

Description	Part Number
2.50mm, 3.70mm CMC Header, Right-Angle, 32 Circuits, 1 Port, Black	<u>643340100</u>

Use with Part(s)

Description	Part Number
CMC Wire Cap for 32 Circuits, CMC Receptacle Mat Sealed	/content/molex/molex-dot- com/us/en/products/product- page.html/643191201.html
CMC 0.635mm Blind Cavity Plug	/content/molex/molex-dot- com/us/en/products/product- page.html/643251010.html
CMC 1.50mm Blind Cavity Plug	/content/molex/molex-dot- com/us/en/products/product- page.html/643251023.html
CMC CP Female Terminals	64322

1.50mm CMC CP Female Terminals	64323
--------------------------------	-------

Application Tooling

Global

Description	Part Number
Continuity Test Pen Assembly	638121100
Unlocking Tool for CMC and CMX Receptacle Connector	638241200

This document was generated on Apr 11, 2024