

Part Number: 5016461000

**Product Description :** 2.00mm Pitch, iGrid Receptacle Crimp Housing, Dual Row, Positive

Lock, 10 Circuits, Natural

Status: Active

Series Number: 501646

**Product Category:** Connector Housings

#### **Documents & Resources**

#### **Drawings**

Drawing 5016461000\_sd.pdf

#### 3D Models and Design Files

2D Drawing DXF 5016461000.dxf

2D Drawing DXF (PDF) 5016461000.pdf

3D Model 5016461000\_stp.zip

#### **Specifications**

Application Specification 5016460000-A00.pdf
Application Specification 5016460000-A01.pdf
Packaging Specification 5016469200-200.pdf
Product Specification 5016460000-PS-000.pdf
Product Specification 5016461000-PS-000.pdf
Product Specification 5016461001-PS-001.pdf
Product Specification PS-501646-001-001.pdf

## **Product Environment Compliance**

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>©</b>
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

## **Part Details**

#### General

Status	Active
Category	Connector Housings
Series	501646
Description	2.00mm Pitch, iGrid Receptacle Crimp Housing, Dual Row, Positive Lock, 10 Circuits, Natural
Application	Signal, Wire-to-Board
Product Family	iGrid Wire-to-Board Dual-Row System
Product Name	iGrid
UPC	822350087131

# Agency

CSA	LR19980
UL	E29179

## **Physical**

Circuits (maximum)	10
Color - Resin	Natural
Flammability	94V-0
Gender	Receptacle
Glow-Wire Capable	No
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Resin	Nylon
Net Weight	360.000/mg
Number of Rows	2

Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	2.00mm
Pitch - Termination Interface	2.00mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40° to +105°C

## Mates With / Use With

# Mates with Part(s)

Description	Part Number
iGrid Vertical, Dual Row, Through Hole Headers	501645
iGrid Vertical, Dual Row, Through Hole Headers	503091
iGrid Right-Angle, Dual Row, Through Hole Headers	501876
iGrid Right-Angle, Dual Row, Through Hole Headers	208659

# Use with Part(s)

Description	Part Number
iGrid Female Crimp Terminals	<u>501647</u>
iGrid Female Crimp Terminals	501648
iGrid Female Crimp Terminals	503095

This document was generated on Jun 08, 2024