

Part Number: 5054321201

Product Description : 1.25mm Pitch, Micro-Lock Plus Receptacle Crimp Housing, Dual

Row, Positive Lock, 12 Circuits, Black

Status: Active

Series Number: 505432

Product Category: Connector Housings

Documents & Resources

Drawings

Drawing 5054321201_sd.pdf

3D Models and Design Files

2D Drawing DXF 5054321201.dxf

2D Drawing DXF (PDF) 5054321201.pdf

3D Model 5054321201_stp.zip

Specifications

Application Specification 5054320000-AS-000.pdf

Packaging Specification 5054329200-200.pdf

Product Specification 5054320000-002.pdf

Product Specification 5054320000-005.pdf

Product Specification 5054320000-006.pdf

Product Specification 5054321000-PS-002.pdf

Product Specification 5054321000-PS-006.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	©
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2- 21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC

- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Connector Housings
Series	505432
Description	1.25mm Pitch, Micro-Lock Plus Receptacle Crimp Housing, Dual Row, Positive Lock, 12 Circuits, Black
Application	Signal, Wire-to-Board
Product Family	Micro-Lock Connector System
Product Name	Micro-Lock Plus
UPC	889056764889

Agency

UL	E29179

Physical

Circuits (maximum)	12
Color - Resin	Black
Gender	Receptacle
Glow-Wire Capable	No
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Resin	Polyester
Net Weight	296.050/mg
Number of Rows	2

Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	1.25mm
Pitch - Termination Interface	1.25mm
Polarized to Mating Part	Yes
Temperature Range - Operating	-40° to +105°C

Mates With / Use With

Mates with Part(s)

Description	Part Number
1.25mm Pitch Micro-Lock Plus Vertical, Dual Row, Surface Mount Headers	505433
1.25mm Pitch Micro-Lock Plus Right-Angle, Dual Row, Surface Mount Headers	505448

Use with Part(s)

Description	Part Number
Pre-Crimped Lead Micro-Lock Plus Female-to-Micro-Lock Plus Female, Tin (Sn) Plating, 150.00mm Length, 26 AWG, Black	/content/molex/molex-dot- com/us/en/products/product- page.html/797581148.html
Pre-Crimped Lead Micro-Lock Plus Female-to-Micro-Lock Plus Female, Tin (Sn) Plating, 300.00mm Length, 26 AWG, Black	/content/molex/molex-dot- com/us/en/products/product- page.html//97581149.html
Pre-Crimped Lead Micro-Lock Plus Female-to-Micro-Lock Plus Female, Gold (Au) Plating, 150.00mm Length, 26 AWG, Black	/content/molex/molex-dot- com/us/en/products/product- page.html/797582143.html
Pre-Crimped Lead Micro-Lock Plus Female-to-Micro-Lock Plus Female, Gold (Au) Plating, 300.00mm Length, 26 AWG, Black	/content/molex/molex-dot- com/us/en/products/product- page.html/797582144.html
Micro-Lock Plus Female Crimp Terminals	505431