

AMP

TE Internal #: 54489-2

Rectangular Power Connectors, Housing, Plug / Receptacle, Wireto-Wire / Wire-to-Panel, 2 Position, 7.92 mm [.312 in] Centerline,

Wire & Cable

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors











Rectangular Power Connector Type: Housing
Connector & Housing Type: Plug, Receptacle
Connector System: Wire-to-Panel, Wire-to-Wire

Number of Positions: 2

Centerline (Pitch): 7.92 mm [.312 in]

Features

Product Type Features

Rectangular Power Connector Type	Housing
Connector & Housing Type	Plug, Receptacle
Connector System	Wire-to-Panel, Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Number of Positions	2
Number of Power Positions	2
Number of Signal Positions	0
Number of Rows	1

Electrical Characteristics

Operating Voltage	600 VDC	

Contact Features



Contact Current Rating (Max)	53 A
Contact Retention Within Housing	With
Contact Type	Blade
Termination Features	
Termination Method to Wire & Cable	Crimp & Solder
Mechanical Attachment	
Connector Mounting Type	Panel Mount
Housing Features	
Centerline (Pitch)	7.92 mm[.312 in]
Housing Material	Nylon
Dimensions	
Connector Height	7.92 mm[.312 in]
Product Width	28.55 mm[1.124 in]
Product Length	24.51 mm[.965 in]
Wire Size	10 - 6 AWG
Usage Conditions	
Operating Temperature Range	-55 - 85 °C[-67 - 185 °F]
Operation/Application	
Circuit Application	Power
Industry Standards	
CSA Rating	Certified, LR 7189
UL Rating	Recognized
Compatible With Agency/Standards Products	CSA, UL
Compatible With Approved Standards Products	UL E28476
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	200
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought





















Documents

Product Drawings

HSG ASSY,PWR LK,SRS1,2POS,FLNG

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_54489-2_L.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_54489-2_L.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_54489-2_L.3d_stp.zip

English

3D PDF

English

Customer View Model

ENG_CVM_54489-2_E.2d_dxf.zip

English

Customer View Model

ENG_CVM_54489-2_E.3d_igs.zip

English

Customer View Model

ENG_CVM_54489-2_E.3d_stp.zip

English



By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

Product Specifications

Application Specification

English

Application Specification

Japanese

Power-Lock 75 Series Contacts

Japanese

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

Agency Approval Document

English