


28.6





PLUG, 3 SOCKET, AT SERIES, REDUCED DIA. SEAL

AT06-3S-RD01XXX

ծ

STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLORS SHOWN IN PART NUMBER CHART ARE AVAILABLE VIA SPECIAL ORDER.


NOTES: UNLESS	OTHEDWICE	CDECIEIED
INUTEO. UNLEGO	CIDERWISE	SECULIED

1. MATERIAL:


HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: REDUCED DIAMETER WIRE SEAL
- 3. SPECIFICATIONS:
  - 3.1 CURRENT RATING: 13 AMPS
  - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
  - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
  - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
  - 3.5 MOISTURE RESISTANCE:
    - IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION) IP69K(MATED CONDITION)
  - 3.6 MATING CYCLE DURABILITY: 100 CYCLES
  - 3.7 RoHS COMPLIANT
- 4. MATING PART: AT04-3P\* RECEPTACLE (\* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

6	CONTACT	SIZE AND RE	AR SEAL WIF	RE RANGE:
	CONTACT SIZE	MIN. INSUL O.D.	MAX. INSUL O.D.	TYPICAL WIRE RANGE
	16	1.35 mm (.053 in)	3.05 mm (.120 in)	14 - 20 AWG (2.0-0.5mm <sup>2</sup> )



	SEE PART N	E PART NUMBER CHART		REF: DT06-3S-C015, DT06-3S-CE02, DT06-3S-CE06			1		
	PART N	IUMBER			DE	SCRIPTION		ITEM	-
QUANTITY		ı	MAT	ERI	ALS LI	ST			H
UNLESS OTHER	WISE SPECIFIED	SIGN	ATURES	DATE	^	mnha	\nol		
2) Tolerances are a 1 PL DEC ±0.30		DRAWN:	LOUIE	23NOV20		mphe			
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:	ORION	25NOV20	Sir	e Systems - www.amphe	nol-sine.com	—	
3) Note reference	- X	ENGINEER:				44724 Morley Drive			
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMY	27NOV20		Clinton Township, MI 48	1036		-
		CUSTOMER:				JG, 3 SOCKET, AT	,		
			3 IS SUPPLIED F		REDI	JCED DIAMETER	WIRE SEAL		
PROCESS SPECIFICA	TIONS:	SPECIFICATIO SHOWN HERE THE AMPHENO OF REPRODUC	NS AND PERFOR ON ARE THE PR DL CORPORATIO CTION ARE IMPL ARE SUBJECT TO	RMANCE DATA OPERTY OF DN. NO RIGHTS IED. ALL	B C-	AT06-3S-RE		A5	
NEXT ASS'Y:			ING VARIATIONS		SCALE: NONE		SHEET 1 OF	1	



## A Series™ - Contact Size 16 Options (Works with: AT, ATV, AHD-9, ARC, DuraMate and PanelMate Series)

	Machined Contacts, Sockets & Pins			
Part Number	Description	Size	AWG	Туре
AT60-215-1631	Male Contact - Pin, Gold-plated	16	14	Machined
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined
AT60-202-1631	Male Contact - Pin, Gold-plated	16	16-20	Machined
AT62-201-1631	Female Contact - Socket, Gold-plated	16	16-20	Machined
AT60-202-16141	Male Contact - Pin, Nickel-plated	16	16-20	Machined
AT62-201-16141	Female Contact - Socket, Nickel-plated	16	16-20	Machined
AT60-202-1631-22	Male Contact - Pin, Gold-plated	16	22-24	Machined
AT62-201-1631-22	Female Contact - Socket, Gold-plated	16	22-24	Machined
AT60-202-16141-22	Male Contact - Pin, Nickel-plated	16	22-24	Machined
AT62-201-16141-22	Female Contact - Socket, Nickel-plated	16	22-24	Machined

Tooling - Machined Contacts		
Part Number	Description	
AUTK-16	Hand Crimp Tool, Size 16	
AUTK-100	Universal Heavy Duty Contact Crimping Tool Kit, Size 12/16/20	
CA-5D12	Universal Hand Crimp Tool, Size 12/16/20	
CA-5E12	Pneumatic Crimp Tool, Size 12/16/20	

Contact Removal Tools (For both Machined or Stamped & Formed Contacts)		
Part Number	Description	
ATRT-100	Contact and Wedgelock Extraction Tool	
AT11-310-1605	Contact Removal Tool, Plastic, Size 16	

Sealing Plugs (For both Machined or Stamped & Formed Contacts)		
Part Number	Description	
A114017	Sealing Plug, Size 16, White	
A114017-SR	Sealing Plug, Size 16, SR01 Series, Black	
AT13-217-1605	Locking Sealing Plug, Size 16, Grey	
AT13-217-1605-SR	Locking Sealing Plug, Size 16, SR01 Series, Red	

Stamped & Formed Contacts, Sockets & Pins				
Description	Size	AWG	Туре	
Male Contact - Pin, Nickel-plated	16	14-18	Stamped & Formed	
Female Contact - Socket, Nickel-plated	16	14-18	Stamped & Formed	
Male Contact - Pin, Gold-plated	16	14-18	Stamped & Formed	
Female Contact - Socket, Gold-plated	16	14-18	Stamped & Formed	
Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed	
Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed	
Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed	
Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed	
Male Contact - Pin, Nickel-plated	16	16-20	Stamped & Formed	
Female Contact - Socket, Nickel-plated	16	16-20	Stamped & Formed	
Male Contact - Pin, Gold-plated	16	16-20	Stamped & Formed	
Female Contact - Socket, Gold-plated	16	16-20	Stamped & Formed	
Male Contact - Pin, Tin-plated	16	16-20	Stamped & Formed	
Female Contact - Socket, Tin-plated	16	16-20	Stamped & Formed	
Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed	
Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed	
Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed	
Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed	
	Description  Male Contact - Pin, Nickel-plated Female Contact - Socket, Nickel-plated Male Contact - Pin, Gold-plated Female Contact - Socket, Gold-plated Male Contact - Pin, Nickel-plated Male Contact - Pin, Nickel-plated Male Contact - Socket, Nickel-plated Male Contact - Socket, Nickel-plated Male Contact - Socket, Gold-plated Female Contact - Socket, Gold-plated Male Contact - Pin, Nickel-plated Female Contact - Socket, Nickel-plated Male Contact - Pin, Gold-plated Female Contact - Socket, Gold-plated Male Contact - Pin, Tin-plated Female Contact - Pin, Tin-plated Male Contact - Pin, Nickel-plated Male Contact - Pin, Gold-plated	DescriptionSizeMale Contact - Pin, Nickel-plated16Female Contact - Socket, Nickel-plated16Male Contact - Pin, Gold-plated16Female Contact - Socket, Gold-plated16Male Contact - Pin, Nickel-plated16Female Contact - Pin, Nickel-plated16Male Contact - Pin, Gold-plated16Female Contact - Pin, Gold-plated16Male Contact - Pin, Mickel-plated16Female Contact - Socket, Gold-plated16Female Contact - Pin, Nickel-plated16Male Contact - Pin, Gold-plated16Female Contact - Socket, Gold-plated16Male Contact - Pin, Tin-plated16Female Contact - Pin, Tin-plated16Male Contact - Pin, Nickel-plated16Male Contact - Pin, Nickel-plated16Female Contact - Socket, Nickel-plated16Male Contact - Pin, Nickel-plated16Male Contact - Pin, Nickel-plated16Male Contact - Pin, Gold-plated16	DescriptionSizeAWGMale Contact - Pin, Nickel-plated1614-18Female Contact - Socket, Nickel-plated1614-18Male Contact - Pin, Gold-plated1614-18Female Contact - Socket, Gold-plated1614-18Male Contact - Pin, Nickel-plated1616-18Female Contact - Socket, Nickel-plated1616-18Male Contact - Pin, Gold-plated1616-18Female Contact - Socket, Gold-plated1616-18Male Contact - Pin, Nickel-plated1616-20Female Contact - Socket, Nickel-plated1616-20Male Contact - Pin, Gold-plated1616-20Female Contact - Socket, Gold-plated1616-20Male Contact - Pin, Tin-plated1616-20Female Contact - Pin, Tin-plated1616-20Male Contact - Pin, Nickel-plated1616-20Male Contact - Socket, Tin-plated1616-20Male Contact - Pin, Nickel-plated1620-22Female Contact - Socket, Nickel-plated1620-22Male Contact - Pin, Gold-plated1620-22	

	Tooling - Stamped & Formed Contacts
MFX-3950	Crimp Die - Size 16, 18-20AWG
MFX-3953	Crimp Die - Size 16, 16-18AWG
MFX-3975	Crimp Die - Size 16, 14-16AWG
MFX-3990	Crimp Die - Size 16, 20-22AWG
ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG
ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG
ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG