70-725-1

Socket, SE Relays, 30A, 6 pins, screw connectors, separate contact, for 725 power relay



Main

Product Range	Harmony Electromechanical Relays
Product Type	Socket
Number of Terminals	6
Switch Function	DPST
Contact Composition	2 NO

Complementary

Rated Current	30 A
[Ue] rated operational voltage	300 V
Connections Terminals	Screw terminal, clamping connection capacity:6 mm², AWG 10 solid Screw terminal, clamping connection capacity:2 x 0.52 x 6 mm², AWG 20AWG 10 stranded
Tightening Torque	Screw 1.2 N.m
Fixing Mode	Clip-on 35 mm symmetrical DIN rail
Product Weight	2.36 oz (67 g)
Depth	2.78 in (70.5 mm)

Environment

Flame Retardance	UL94-V0


Ordering and shipping details

or worming surve or inppining statement		
Category	US10CP221127	
Discount Schedule	0CP2	
GTIN	3606480277986	
Returnability	No	
Country of origin	CN	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.79 in (7.08 cm)	
Package 1 Width	2.13 in (5.4 cm)	
Package 1 Length	0.93 in (2.35 cm)	
Package 1 Weight	2.36 oz (67 g)	

Dimensions



Wiring Diagram

