

COAXIAL SURGE PROTECTOR DEVICE, GDT technology up to 1.0 GHz
3401.01.F

Properties

- Broadband frequency operation from DC to 1 GHz
- Gas discharge tube replaceable and not included
- DC/AC remote powering via coaxial same cable
- Surge current handling capability 30 kA once and 20 kA multiple
- Semper self-extinguishing functionality optional



Product configuration	
Main path connectors	Port 1: unprotected, BNC jack (female)
	Port 2: protected, BNC jack (female)
Mounting and grounding	MH12 (bulkhead mounting)
Side of bulkhead	protected side
Capsule holder with chain	YES
EMP can be install reversed	YES

Interface and material data	
Housing material / plating	Brass / SUCOPLATE (R) Plating
Center contact, material / plating	Port 1: Copper Beryllium Alloy / Gold Plating (without Nickel underplating)
	Port 2: Copper Beryllium Alloy / Gold Plating (without Nickel underplating)

Electrical data	
Impedance	50 Ω
Frequency frame	0 MHz to 1000 MHz
Return loss typical	19 dB
Insertion loss typical	0.1 dB
CW power frame	150 W
Residual pulse energy (typ.)	350 μJ (test pulse 4 kV 1.2/50 μs; 2 kA 8/20 μs)
Residual pulse voltage (typ.)	650 V (test pulse 4 kV 1.2/50 μs; 2 kA 8/20 μs)
Surge current handling capability	30 kA single, 20 kA multiple (test pulse 8/20 μs)

COAXIAL SURGE PROTECTOR DEVICE, GDT technology up to 1.0 GHz

3401.01.F

Electrical bands	
	Range 1
Frequency range	0 MHz ... 300 MHz
Return loss	26.44 dB
Insertion loss	0.1 dB
Power avg. / peak	150 W / -
Electrical remarks	
Gas tube	Yes DC, GDT not included
Electrical remarks	Data refer to GDT 9071.99.0547, 230 V
Mechanical data	
Weight	80 g
Mating cycles	500
Environmental data	
Operation temperature	-40 °C ... 85 °C
Storage temperature	-40 °C ... 85 °C
Ingress protection (IP Rating)	IP65
Thermal shock according	MIL-STD-202, Method 107, Cond. B
Vibration according	MIL-STD-202, Method 204, Cond. D
Moisture resistance according	MIL-STD-202, Method 106
Comment	
NATO Stock Number	5920-12-310-6281
Ordering Information Table	
Item number	Item description
22643327	3401.01.F

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2038 / Date of publication: 24.04.2024 / uncontrolled copy