



0.5 Watts Low Power WR-34 Waveguide
Load 22 GHz to 33 GHz, Aluminum

Waveguide Terminations Technical Data Sheet

PE6801

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	22		33	GHz
VSWR			1.25:1	
Input Power (CW)			0.5	Watts

Mechanical Specifications

Size	
Length	0.705 in [17.91 mm]
Width/Dia.	0.875 in [22.23 mm]
Height	0.875 in [22.23 mm]
Weight	0.0252 lbs [11.43 g]

Description	Flange	Waveguide
Designation	None	WR-34
Type	Square Cover	
Material		Aluminum

Environmental Specifications

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:


0.5 Watts Low Power WR-34 Waveguide Load 22 GHz to 33 GHz, Aluminum from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [0.5 Watts Low Power WR-34 Waveguide Load 22 GHz to 33 GHz, Aluminum PE6801](#)

URL: <https://www.pasternack.com/waveguide-termination-frequency-range-2200-3300-ghz-pe6801-p.aspx>

PE6801 CAD Drawing

0.5 Watts Low Power WR-34 Waveguide Load 22 GHz to 33 GHz, Aluminum



NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE	PE6801
CAGE CODE	53919
CAD FILE	01/02/19
SCALE	N/A
SIZE	A
	7361

PASTERNACK®
THE ENGINEER'S RF SOURCE
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com