



WR-34 Waveguide Rotary Joint, UG Cover Flanges, L-Style in Brass

TECHNICAL DATA SHEET

PEW34RJ0001

Features

- WR-34 Waveguide
- Operating Frequency Range from 29.4 GHz to 31 GHz
- UG Cover/UG Cover Flanges
- L-Style Configuration
- 1.25:1 Max VSWR
- 100 Watts (CW) Max Power Handling
- Insertion loss(Max): 0.35 dB
- Rotating Speed (Max): 30 RPM
- Lifetime (Min): 500 x 10⁴ Revolutions

Applications

- Radar Systems
- Military and Space
- Wireless Radio Systems
- Communication Systems
- R&D Labs
- Maritime Waveguide Systems

Description

Waveguide rotary joints are used to connect waveguide components which need to rotate or change orientation during operation within a waveguide system. Designed to perform in harsh operating environment, PEW34RJ001 from Pasternack is a WR-34 waveguide rotary joint that operates in the frequency range of 29.4 GHz to 31 GHz. This WR-34 waveguide rotary joint has a Max VSWR of 1.25:1. This waveguide rotary joint is made of painted brass and incorporates UG Cover/UG Cover flange interface with maximum rotary speed of 30 RPM and minimum life time of 500 x 10⁴ Revolutions. Waveguide rotary joints are part of Pasternack's comprehensive waveguide product offerings which are available in stock and ready for same-day shipment.

Electrical Specifications (Values at 25°C, sea level)

Description	Minimum	Typical	Maximum	Units
Frequency Range	29.4		31	GHz
VSWR			1.25:1	
VSWR 1, Rotational Variance			0.05	
Insertion Loss			0.35	dB
Input Power (CW)			100	Watts
Peak Power			500	Watts
Insertion Loss Rotational Variance			0.05	dB
Phase Rotational Variance			3	Degrees

Mechanical Specifications

Description	Minimum	Typical	Maximum	Units
Temperature				
Operating Temperature		-40 to 70 °C		
Storage Temperature		-55 to 85 °C		
Humidity		85% (Max)		

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-34 Waveguide Rotary Joint, UG Cover Flanges, L-Style in Brass PEW34RJ0001](#)



WR-34 Waveguide Rotary Joint, UG
Cover Flanges, L-Style in Brass

TECHNICAL DATA SHEET

PEW34RJ0001

Size

Weight 0.0622 lbs [28.21 g]

Interface

Waveguide Size	WR-34
Flange Type 1	UG Cover
Flange Type 2	UG Cover
Body Material and Plating	Brass, Paint
Rotating Speed	30 RPM
Lifetime	500 x 10 ⁴ Revolutions
Starting Torque	1.77 in-lbs [0.2 Nm]
Torque During Rotation	0.88 in-lbs [0.1 Nm]
IP Protection Level	IP54

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

WR-34 Waveguide Rotary Joint, UG Cover Flanges, L-Style in Brass from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-34 Waveguide Rotary Joint, UG Cover Flanges, L-Style in Brass PEW34RJ0001](#)

URL: <https://www.pasternack.com/pew34rj0001-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PEW34RJ0001 CAD Drawing

WR-34 Waveguide Rotary Joint, UG Cover Flanges, L-Style in Brass

