



WR-34 UG-1530/U Square Cover Flange to 2.92mm Female Waveguide to Coax Adapter Operating From 22 GHz to 33 GHz

Waveguide to Coax Adapters Technical Data Sheet

PEWCA1021

Features

- 22 to 33 GHz Frequency Range
- WR-34 Waveguide Interface with UG-1530/U Square Cover Flange
- 2.92mm Female RF Interface

 Comprehensive waveguide offerings also include E-Bends, H-Bends, Sections, Filters, Terminations, Couplers, and more.

Applications

- Test Benches
- Radar

- Satellite
- · Microwave Radio Systems
- Military and Space
- Communication Systems

Description

The PEWCA1021 is a waveguide to coaxial adapter operating in the 22 to 33 GHz frequency range. This adapter offers a WR-34 waveguide interface size coupled with a precision tolerance UG-1530/U Square Cover flange. The PEWCA1021 is constructed of aluminum to ensure durability and repeatable RF performance. The coaxial connection offered by this adapter uses a 2.92mm Female connector.

Configuration

Waveguide Size Flange RF Connector Body Geometry WR-34 UG-1530/U Square Cover 2.92mm Female Right Angle

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	22		33	GHz
VSWR			1.25:1	
Insertion Loss		0.3		dB

Mechanical Specifications

RF Connector

Connector Type 2.92mm Female

Waveguide Interface

Waveguide Type WR-34
Flange Type Square Cover
Flange Designation UG-1530/U

Body Material and Plating Aluminum, Chem Film

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: WR-34 UG-1530/U Square Cover Flange to 2.92mm Female Waveguide to Coax Adapter Operating From 22 GHz to 33 GHz PEWCA1021

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com





WR-34 UG-1530/U Square Cover Flange to 2.92mm Female Waveguide to Coax Adapter Operating From 22 GHz to 33 GHz

Waveguide to Coax Adapters Technical Data Sheet

PEWCA1021


Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

• Values at +25 °C, sea level unless stated otherwise

Typical Performance Data



WR-34 UG-1530/U Square Cover Flange to 2.92mm Female Waveguide to Coax Adapter Operating From 22 GHz to 33 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: WR-34 UG-1530/U Square Cover Flange to 2.92mm Female Waveguide to Coax Adapter Operating From 22 GHz to 33 GHz PEWCA1021

URL: https://www.pasternack.com/wr-34-ug1530-square-2.92mm-female-waveguide-coax-adapter-pewca1021-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

PEWCA1021 CAD Drawing

WR-34 UG-1530/U Square Cover Flange to 2.92mm Female Waveguide to Coax Adapter Operating From 22 GHz to 33 GHz

