Wi-Fi / Bluetooth

ST0243-00-N01-U

Amphenol

Datasheet

2.4-2.5GHz

Chip antenna

Features:

High performing Wi-Fi & Bluetooth antenna with SMT mounting on PCB.



 $2 \times 1.2 \times 0.6$ mm

Chip Antenna

Peak Gain (dBi)

Efficiency (%)

Average Gain (dB)

Applications:

- CPE Router, Set-top boxes & Gateway
- loT devices
- Wi-Fi & Bluetooth Mesh
- Smart Metering
- Robotics



Electrical Specifications Antenna Characteristics Radiation Pattern Polarization Antenna Type Max. Input Power **Impedance** Chip Antenna Omni Linear 2W 50Ω Frequency (GHz) 2.4~2.5 Return Loss (dB)@ Center Frequency < -10 Typ.

3.3

-3.1

49


Wi-Fi / Bluetooth ST0243-00-N01-U

Amphenol

Mechanical Specifications				
Mechanical Mechanical				
Dimension (mm)	2.0 × 1.2 × 0.6			
Material	Ceramic			
Weight (g)	0.006			


Environmental				
Temperature Range (°C)	-40 to 85			
Humidity	Non-condensing 65°C 95% RH			
RoHS Compliant				

Mechanical Drawing



Front View

PIN Definitions



Top View

Bottom View

Pin	Soldering PAD	
1	Signal Input	
2	Tuning/Signal Output	

ST0243-00-N01-U


Unit: mm

Wi-Fi / Bluetooth


ST0243-00-N01-U

Amphenol


Antenna Testing Includes Evaluation Board



Test setup, measurement performed in 3D anechoic chamber.




Blue background represents frequency response.




Amphenol

Radiation Pattern - Free Space


XY - Plane



YZ - Plane




XZ - Plane





Amphenol

Matching Circuit Design




- * To make the antenna have this resonance must be matched with the matching circuit.
- * The matching component may be slightly different than that shown depending on the distance to the ground plane, the dielectric constant of the PCB, and PCB material thickness.

Circuit Matching Components					
Circuit Symbol	Size	Description			
1	0402	None			
2	0402	0.5 pF Capacitor			
3	0402	0.8 pF Capacitor			
4	0402	2 pF Capacitor			
DC Block	0402	22 pF Capacitor			

Wi-Fi / Bluetooth ST0243-00-N01-U


Amphenol

Clearance Area Design



Evaluation Board

Unit: mm



Base Material : FR-4, T=1.0




Amphenol

Recommended Reflow Temperature Profile

Recommended solder paste alloy:

SAC305 (Sn96.5 /Ag3 /Cu0.5) Lead Free solder paste



Wi-Fi / Bluetooth ST0243-00-N01-U

Amphenol

Revisions						
Rev.	Description	Date	ECN	Approval		
Α	Initial Release	2023-02-21	ST0243-00-N01-U-RA00	ATC		

NOTICE - These drawings, specifications, or other data (I) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.