

6 dBi Omni Antenna 900-928 MHz, N Type Female Fiberglass Radome, 1.5:1 Typ VSWR

The Fairview Microwave FM510M1015 is a high performance omnidirectional antenna designed for the 900 MHz ISM band. It is ideally suited for multipoint, Non Line of Sight (NLOS) and mobile applications where high gain and wide coverage is desired. Typical applications include 900MHz Wireless LAN, SCADA, Wireless Video Links, LPWAN/IoT/M2M, and 900MHz Cellular band applications.

This antenna features an integral N-Female type connector that mounts through the wall of an equipment enclosure. Included with the FM510M1015 is a dual u-bolt mast mounting kit. Consisting of a heavy-duty steel bracket and a pair of U-bolts, this kit allows installation on masts up to 2.0" in diameter.

This omni antenna's construction features a rugged 1.58" diameter fiberglass radome for durability, aesthetics and long service life. It is designed for all weather operation.

Configuration

| | |
|----------------------|-----------|
| Design | Omni |
| Gain | 6 |
| Polarization | Vertical |
| Connector Type | N Female |
| Number of Ports | 1 |
| Lightning Protection | DC Ground |

Electrical Specifications

| Description | Min | Typ | Max | Units |
|---------------------------------|-----|-------|-------|---------|
| Frequency Range | 900 | | 928 | MHz |
| Input VSWR | | 1.5:1 | 1.5:1 | |
| Impedance | | 50 | | Ohms |
| Gain | | 6 | | dBi |
| Horizontal (Azimuth) Beam Width | | 360 | | Degrees |
| Vertical (Elevation) Beam Width | | 19 | | Degrees |
| Input Power | | | 50 | Watts |

Mechanical Specifications

| | |
|-----------------|----------------------|
| Radome Material | Fiberglass |
| Size | |
| Length | 40 in [101.6 cm] |
| Width | 1.7 in [43.18 mm] |
| Height | 1.7 in [43.18 mm] |
| Weight | 1.522 lbs [690.37 g] |

Environmental Specifications

| | |
|--------------------|----------------------|
| Temperature | |
| Operating Range | -40 to +60 deg C |
| Wind Loading | 130 MPH [209.21 KPH] |



Features:

- Rugged industrial grade design
- Lightweight fiberglass radome
- All weather operation
- Integral N-Female connector
- Includes heavy duty steel mast mounting brackets

Applications:

- 900 MHz ISM band
- LPWAN, LoRA, IoT, M2M applications
- GSM, SCADA applications
- 900 MHz cellular band
- Point to multi-point and Non Line Of Sight (NLOS) applications

Fairview Microwave
 301 Leora Ln., Suite 100
 Lewisville, TX 75056
 Tel: 1-800-715-4396 / (972) 649-6678
 Fax: (972) 649-6689
www.fairviewmicrowave.com
sales@fairviewmicrowave.com

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

6 dBi Omni Antenna 900-928 MHz, N Type Female Fiberglass Radome, 1.5:1 Typ VSWR from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [6 dBi Omni Antenna 900-928 MHz, N Type Female Fiberglass Radome, 1.5:1 Typ VSWR FM510M1015](#)

URL: <https://www.fairviewmicrowave.com/6-dbi-omni-antenna-900-928-mhz-n-tyfm-female-1.5-1-ty-p-vswr-fm510m1015-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.

