

27 MHz Omni Antenna 4 dBi Gain, Spring UHF Male Connector



Antennas Technical Data Sheet

PEANOM1067

Features

- · Vertically Polarized
- 4 dBi Gain
- UHF Male Connector

- · Stainless Steel
- 1.5:1 VSWR Max
- · 50 Watt Max Input Power

Applications

- · Offroad/Overland Vehicles
- Mining/Industrial Heavy Equipment
- · Commercial Trucking

- Fleet Management
- Farm Equipment

Description

Pasternack's PEANOM1067 is a vertical polarized antenna that ships same day from our ISO 9001:2015 certified facility. The antenna with 26 to 28 MHz frequency range has a maximum input VSWR of 1.5. This omni directional antenna has UHF male connectors.

This antenna is made of stainless steel, an overall length of 27.56 in, width of 2 in, and weighs 1 lbs. Pasternack's PEANOM1067 is a single band antenna operating from 26 to 28 MHz with 4 dBi gain.

Pasternack's experts are on hand to assist you with any inquiries. Order this PEANOM1067 antenna 7 days a week. 24 hours a day using our on-line ordering system with no MOQs (minimum order quantity) and same-day shipping.

Configuration

Band Type Single

Radiation Pattern Omni Directional

Polarization Vertical Connector Type UHF Male

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	26		28	MHz
Input VSWR			1.5:1	
Impedance		50		Ohms
Gain		4		dBi
Input Power			50	Watts

Mechanical Specifications

Radome Material Stainless Steel

Size

 Overall Length
 27.56 in [700.02 mm]

 Width
 2 in [50.8 mm]

 Height
 2 in [50.8 mm]

 Weight
 1 lbs [453.59 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 27 MHz Omni Antenna 4 dBi Gain, Spring UHF Male Connector PEANOM1067

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



27 MHz Omni Antenna 4 dBi Gain, Spring UHF Male Connector



Antennas Technical Data Sheet

PEANOM1067

Environmental Specifications Temperature

Operating Range

-40 to +80 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

27 MHz Omni Antenna 4 dBi Gain, Spring UHF Male Connector from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 27 MHz Omni Antenna 4 dBi Gain, Spring UHF Male Connector PEANOM1067

URL: https://www.pasternack.com/27-mhz-omni-antenna-4-dbi-gain-spring-uhf-male-connector-peanom1067-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PEANOM1067 CAD Drawing 27 MHz Omni Antenna 4 dBi Gain, Spring UHF Male Connector ш REV INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5 ⋖ APPROVED BY 27 MHZ OMNI ANTENNA 4 DBI, VEHICLE SPRING UHF, 27.5 IN KHIETPAS 1 OF PEANOM1067 NONE \bigoplus CHANGED BY HBAKKE PASTERNACK ITEM NO. Website: www.Pasternack.com Phone: 1.866.727.8376 | 1.949.261.1920 PL259 UHF MALE CONNECTOR 2/28/2023 DATE an INFINIT® brand REVISION N HBAKKE **DRAWN BY** INITIAL RELEASE DESCRIPTION CAGE CODE | 53919 SIZE ⋖ ALL DIMENSIONS ARE FOR REFERENCE ONLY AND SUBJECT TO CHANGE WITHOUT NOTICE. ± 1/32 ANGLES ± 1° <12 [305] = +1 [25] /-0</p>
>12 [305] ≤ 60 [1524] = +2 [51] /-0
>60 [1524] ≤ 120 [3048] = +4 [102] /-0
>120 [3048] ≤ 300 [7620] = +6 [152] /-0 UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILL IMETERS RG58 CABLE FRACTIONS >300 [7620] = +5% / -0 CABLE LENGTH TOLERANCES: REV. ⋖ 157.48 [4000.0] TOLERANCES ZONE $X = \pm .2 \quad [5]$ $XX = \pm .02 \quad [.5]$ $XXX = \pm .005 \quad [.13]$ 25.20 [640.0] THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WITHTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED. 5.65 26.47 [672.4] 2 9 Ω ш Ш \circ Θ ⋖