



**WR-28 Waveguide Dual Polarized Scalar Feed
Horn Antenna, 24 GHz to 40 GHz Frequency
Range, 15 dBi Gain, UG-599/U Flange**

Waveguide Antennas Technical Data Sheet

PEWAN1111

Features

- 24 GHz to 40 GHz Frequency Range
- WR-28 Waveguide
- UG-599/U Threaded Flange
- Dual Linear Polarization
- High Port Isolation
- High Cross-Polarization Rejection

Applications

- 5G Systems
- Radar Systems
- Communication Systems
- Circular and Linear Waveform Separation and Combination

Description

Pasternack's PEWAN1111 is a WR-28 dual polarized scalar feed horn antenna that operates in the frequency range of 24 to 40 GHz. It features an integrated orthomode transducer that provides high port isolation and cross-polarization cancellation and a broad band scalar feed horn that provides low sidelobe levels. The OMT enables the antenna to separate a circular or elliptical polarized waveform into two linear orthogonal waveforms, or vice versa. The antenna supports either vertical or horizontal polarized waveguide forms with a typical 30 dB cross polarization rejections, 15 dBi nominal gain at center frequency, typical 35 dB port isolation between horizontal and vertical ports, typical half power beamwidth of 35 degrees, and -25 dB sidelobe levels. The input of this antenna is a WR-28 waveguide with UG-599/U and 4-40 threaded holes.

Configuration

Design	WR-28 Dual Polarized Scalar Feed Horn
Polarization	Vertical/Horizontal

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	24		40	GHz
Nominal Gain		15		dBi
Horizontal Half Power Beam Width		35		Degrees
Vertical Half Power Beam Width		35		Degrees
VSWR		1.1:1		

Mechanical Specifications

Size	
Length	4.1 in [104.14 mm]
Width	1.6 in [40.64 mm]
Height	0.75 in [19.05 mm]
Weight	0.35 lbs [158.76 g]

Waveguide Interface

Waveguide Size	WR-28
----------------	-------

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-28 Waveguide Dual Polarized Scalar Feed Horn Antenna, 24 GHz to 40 GHz Frequency Range, 15 dBi Gain, UG-599/U Flange PEWAN1111](#)



WR-28 Waveguide Dual Polarized Scalar Feed
Horn Antenna, 24 GHz to 40 GHz Frequency
Range, 15 dBi Gain, UG-599/U Flange

Waveguide Antennas Technical Data Sheet

PEWAN1111

Flange Designation
Body Material and Plating

UG-599/U
Aluminum, Gold

Environmental Specifications

Temperature


Operating Range

-40 to 85 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-28 Waveguide Dual Polarized Scalar Feed Horn Antenna, 24 GHz to 40 GHz Frequency Range, 15 dBi Gain, UG-599/U Flange PEWAN1111](#)



WR-28 Waveguide Dual Polarized Scalar Feed
Horn Antenna, 24 GHz to 40 GHz Frequency
Range, 15 dBi Gain, UG-599/U Flange

Waveguide Antennas Technical Data Sheet

PEWAN1111




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-28 Waveguide Dual Polarized Scalar Feed Horn Antenna, 24 GHz to 40 GHz Frequency Range, 15 dBi Gain, UG-599/U Flange PEWAN1111](#)



WR-28 Waveguide Dual Polarized Scalar Feed
Horn Antenna, 24 GHz to 40 GHz Frequency
Range, 15 dBi Gain, UG-599/U Flange

Waveguide Antennas Technical Data Sheet

PEWAN1111




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-28 Waveguide Dual Polarized Scalar Feed Horn Antenna, 24 GHz to 40 GHz Frequency Range, 15 dBi Gain, UG-599/U Flange PEWAN1111](#)



WR-28 Waveguide Dual Polarized Scalar Feed
Horn Antenna, 24 GHz to 40 GHz Frequency
Range, 15 dBi Gain, UG-599/U Flange

Waveguide Antennas Technical Data Sheet

PEWAN1111



WR-28 Waveguide Dual Polarized Scalar Feed Horn Antenna, 24 GHz to 40 GHz Frequency Range, 15 dBi Gain, UG-599/U Flange from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-28 Waveguide Dual Polarized Scalar Feed Horn Antenna, 24 GHz to 40 GHz Frequency Range, 15 dBi Gain, UG-599/U Flange PEWAN1111](#)

URL: <https://www.pasternack.com/wr-28-waveguide-gain-horn-antenna-15dbi-ug-599-flange-pewan1111-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PEWAN1111 CAD Drawing

WR-28 Waveguide Dual Polarized Scalar Feed Horn Antenna, 24 GHz
to 40 GHz Frequency Range, 15 dBi Gain, UG-599/U Flange

