

## SFI0618S DATA SHEET

# **Isolator SMA Female With 12 dB Isolation From 6 GHz to 18 GHz Rated to 10 Watts**

### **Electrical Specifications**

Description	Min	Тур	Мах	Units
Frequency Range	6		18	GHz
Impedance		50		Ohms
Insertion Loss			2	dB
Isolation	12			dB
VSWR			1.5:1	
Forward Power, CW			10	Watts
Forward Power, Peak			20	Watts
Reverse Power, CW			2	Watts

#### **Mechanical Specifications**

Configuration	
Weight	0.025 lbs [11.34 g]
Height	0.38 in [9.65 mm]
Length Width	1.25 in [31.75 mm] 0.73 in [18.54 mm]
Size	

Design	Single Junction
Connector 1	SMA Female
Connector 2	SMA Female

#### **Environmental Specifications**

**Temperature** Operating Range

+0 to +85 deg C

**Compliance Certifications** (see product page for current document)

#### **Plotted and Other Data**


Notes:

Fairview Microwave 1130 Junction Dr. #100 Allen, TX 75013 Tel: 1-800-715-4396 / (972) 649-6678 Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com









**Typical Performance Data** 


Isolator SMA Female With 12 dB Isolation From 6 GHz to 18 GHz Rated to 10 Watts from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: Isolator SMA Female With 12 dB Isolation From 6 GHz to 18 GHz Rated to 10 Watts SFI0618S

URL: https://www.fairviewmicrowave.com/isolator-sma-female-12db-isolation-18-ghz-10-watts-sfi0618s-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.





SFI0618S DATA SHEET

FAIRVIEW MICROWAVE INC.	NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].					
Isolator SMA Female With 12 dB Isolation From 6 GHz to 18 GHz Rated to 10 Watts	DWG NO SFI0618S			CAGE CODE 3FKR5		
	CAD FILE 100814	SHEET	SCAL	E N/A	SIZE A	2233

1130 Junction Dr. #100 Allen, TX 75013 | Tel: 1-800-715-4396 / (972) 649-6678 / Fax: (972) 649-6689