



WR-15 Waveguide Isolator from 61 GHz to 65 GHz,
15 dB min Isolation, UG-385/U Cover Flange, Brass

Waveguide Isolators Technical Data Sheet

PE-W15IR001

Features

- WR-15 Waveguide Isolator
- V Band Frequency Range 61 to 65 GHz
- UG-385/U Flange Configuration
- Maximum VSWR 1.4:1
- Minimum 15 dB isolation
- Maximum Forward Power 5 W (CW)

Applications

- Radar Systems
- Military
- Wireless Radio Systems
- Telecom Infrastructure
- Communication Systems
- R&D Labs
- Microwave Radio Systems

Description

The PE-W15IR001 is a Waveguide Isolator offering 15 dB minimum isolation over the V band frequency range of 61 to 65 GHz. The design achieves high isolation with wide band performance and the WR-15 waveguide uses UG-385/U Cover compatible flanges on all ports and has a power rating of 5 watts (CW).

Pasternack offers a wide variety of isolators and waveguide isolators to fit your needs. These are two-port devices that transmit microwave or radio frequency power in one direction only and block the signal in the opposite direction. They can be thought of as a diode for RF energy. Isolators are used to isolate equipment from the effects of conditions outside of the equipment. For instance they are used to prevent a microwave source being detuned by a mismatched load. Pasternack's waveguide isolators feature excellent insertion loss, full WR band high isolation and reliability.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	61		65	GHz
Insertion Loss			0.6	dB
Isolation	15			dB
VSWR			1.4:1	
Forward Power (CW)			5	Watts
Forward Power (Peak)			30	Watts
Reverse Power (CW)			0.5	Watts
Reverse Power (Peak)			3	Watts

Mechanical Specifications

Size	
Length	1.06 in [26.92 mm]
Width	0.87 in [22.1 mm]
Height	0.75 in [19.05 mm]
Weight	0.1 lbs [45.36 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-15 Waveguide Isolator from 61 GHz to 65 GHz, 15 dB min Isolation, UG-385/U Cover Flange, Brass PE-W15IR001](#)



WR-15 Waveguide Isolator from 61 GHz to 65 GHz,
15 dB min Isolation, UG-385/U Cover Flange, Brass

Waveguide Isolators Technical Data Sheet

PE-W15IR001

Configuration

Waveguide Size	WR-15
Flange Designation	UG-385/U
Flange Type	Cover
Body Material and Plating	Brass, Gold


Environmental Specifications

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-15 Waveguide Isolator from 61 GHz to 65 GHz, 15 dB min Isolation, UG-385/U Cover Flange, Brass PE-W15IR001](#)



WR-15 Waveguide Isolator from 61 GHz to 65 GHz,
15 dB min Isolation, UG-385/U Cover Flange, Brass

Waveguide Isolators Technical Data Sheet

PE-W15IR001



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-15 Waveguide Isolator from 61 GHz to 65 GHz, 15 dB min Isolation, UG-385/U Cover Flange, Brass PE-W15IR001](#)



WR-15 Waveguide Isolator from 61 GHz to 65 GHz,
15 dB min Isolation, UG-385/U Cover Flange, Brass

Waveguide Isolators Technical Data Sheet

PE-W15IR001

WR-15 Waveguide Isolator from 61 GHz to 65 GHz, 15 dB min Isolation, UG-385/U Cover Flange, Brass from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-15 Waveguide Isolator from 61 GHz to 65 GHz, 15 dB min Isolation, UG-385/U Cover Flange, Brass PE-W15IR001](https://www.pasternack.com/wr12-waveguide-isolator-65ghz-15db-ug385-pe-w15ir001-p.aspx)

URL: <https://www.pasternack.com/wr12-waveguide-isolator-65ghz-15db-ug385-pe-w15ir001-p.aspx>


The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

WR-15 Waveguide Isolator from 61 GHz to 65 GHz, 15 dB min Isolation, UG-385/U Cover Flange, Brass

F	E	D	C	B	A
---	---	---	---	---	---

1

THE
PART
THE
EXP



T-Rev.D2