



Directional 30 dB N Coupler from 300 MHz
to 500 MHz Rated to 300 Watts

Couplers Technical Data Sheet

PE2CP1138-30

Features

- Directional Coupler
- N Female Connectorized Design
- 300 to 500 MHz Frequency Range
- Coupling 30 dB
- Directivity > 20 dB
- VSWR < 1.2:1
- Max Power 300 Watts (CW)

Applications

- Test and Measurement
- Military Communications
- Commercial Communications
- Wireless Communications
- SATCOM

Description

Directional couplers are indispensable components for isolating, separating and combining signals. For example, they provide a simple way of sampling microwave signals. They also can make accurate attenuator measurements since reflections are eliminated. The PE2CP1138-30 is a 30 dB directional coupler that operates from 300 to 500 MHz and can handle up to 300 Watts (CW) with 20 dB directivity minimum and 1.2:1 VSWR maximum. The package interface uses N female connectors.

The PE2CP1138-30 is part of Pasternack's family of directional/dual-directional couplers that offer coupling ratios up to 50 dB with excellent performance featuring high directivity, low insertion loss and VSWR. They are available in both narrow and broad bandwidths and can be used in a wide variety of applications including signal sampling, VSWR measurements, power combining and distribution.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	300		500	MHz
Impedance		50		Ohms
Coupling		30		dB
Frequency Sensitivity		±0.5	±0.8	dB
Insertion Loss		0.1	0.2	dB
Directivity	20	22		dB
Main Line VSWR		1.1:1	1.2:1	
Secondary Line VSWR		1.1:1	1.2:1	
Input Power (CW)			300	Watts
Input Power (Peak)			5	kWatts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Directional 30 dB N Coupler from 300 MHz to 500 MHz Rated to 300 Watts PE2CP1138-30](#)



Directional 30 dB N Coupler from 300 MHz
to 500 MHz Rated to 300 Watts

Couplers Technical Data Sheet

PE2CP1138-30

Mechanical Specifications

Size

Length	12.012 in [305.1 mm]
Width/Dia.	2.145 in [54.48 mm]
Height	1.092 in [27.74 mm]
Weight	1.68 lbs [762.04 g]
Housing Material and Plating	Aluminum

Configuration

Input Connector	N Female
Output Connector	N Female
Coupled Connectors	N Female

Environmental Specifications

Temperature

Operating Range	-40 to +85 deg C
Storage Range	-50 to +105 deg C

Humidity	100% RH at 35°C, 95%RH at 40°C
Shock	20G for 11msec half sine wave, 3 axis both directions
Vibration	25g RMS (15 degrees 2KHz) endurance, 1 hour per axis
Altitude	30,000 ft.

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Directional 30 dB N Coupler from 300 MHz to 500 MHz Rated to 300 Watts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Directional 30 dB N Coupler from 300 MHz to 500 MHz Rated to 300 Watts PE2CP1138-30](#)

URL: <https://www.pasternack.com/directional-30-db-coupler-300-mhz-to-500-mhz-pe2cp1138-30-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Directional 30 dB N Coupler from 300 MHz to 500 MHz Rated to 300 Watts

