

TE Internal #: CONMCX004

MCX RF Interface, Jack, 50 Ω , Snap-On, 6 GHz Operating

Frequency, 1 Position, Printed Circuit Board, Panel Mount, -65 - 165

°C [-85 - 329 °F], Solder

View on TE.com >



Connectors > RF Connectors > Coax Connectors



RF Interface: MCX

RF Connector Style: **Jack**

Impedance: 50Ω

RF Connector Coupling Mechanism: Snap-On

Operating Frequency: 6 GHz

Features

Product Type Features

Connector Product Type	Connector Assembly
RF Interface	MCX
RF Connector Style	Jack
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	1	
Number of Coaxial Contacts	1	

Electrical Characteristics

Impedance	50 Ω
-----------	------

Body Features

Cable Connector Orientation Straight	
Body Material Brass	
Body Material Finish Plated	
Body Plating Material Gold	

Contact Features

RF Connector Center Contact Plating Material	Gold
RF Connector Center Contact Material	Beryllium Copper



Termination Features

Termination Method to Wire & Cable	Solder
Mechanical Attachment	
RF Connector Coupling Mechanism	Snap-On
Connector Mounting Type	Panel Mount
RF Contact Captivation Method	Mechanical
Detent	Without
Usage Conditions	
Operating Temperature Range	-65 - 165 °C[-85 - 329 °F]
Operation/Application	
Circuit Application	Signal
Operating Frequency	6 GHz
Packaging Features	
Packaging Quantity	100
Packaging Method	Bulk
Other	
Lockwasher Material	Brass
Dielectric Material	PTFE

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Not Yet Reviewed
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these

MCX RF Interface, Jack, 50 Ω , Snap-On, 6 GHz Operating Frequency, 1 Position, Printed Circuit Board, Panel Mount, -65 - 165 °C [-85 - 329 °F], Solder



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



Documents

CAD Files

Customer View Model

ENG_CVM_CVM_CONMCX004_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_CONMCX004_C.3d_igs.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_CONMCX004_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

Datasheets & Catalog Pages

MCX FEMALE BULKHEAD FRONT MOUNT WITH SOLDER POT

English