

CLF3H0060-10; CLF3H0060S-10

Broadband RF power GaN HEMT

AMPLEON

Rev. 1 — 17 July 2023

Product data sheet

1. Product profile

1.1 General description

The CLF3H0060-10 and CLF3H0060S-10 are 10 W general purpose, unmatched broadband GaN-SiC HEMT transistors that are usable in the frequency range from DC to 6.0 GHz. The device utilizes a thermally enhanced package which supports both CW and pulsed applications.

Table 1. Typical performance

RF performance at $T_{case} = 25\text{ °C}$; $V_{DS} = 50\text{ V}$; $I_{Dq} = 30\text{ mA}$; in a class-AB narrowband production circuit.

Test signal	V_{DS}	f	P_L	G_p	η_D
	(V)	(MHz)	(W)	(dB)	(%)
pulsed CW [1]	50	2500	10	20.1	63

[1] $t_p = 100\text{ }\mu\text{s}$; $\delta = 10\text{ }\%$.

Table 2. Typical performance

RF performance at $T_{case} = 25\text{ °C}$; $V_{DS} = 50\text{ V}$; $I_{Dq} = 30\text{ mA}$; in a common source class-AB test circuit.

Test signal	f	P_L	VSWR	Test voltage	Result
	(MHz)	(W)		(V)	
pulsed CW [1]	2500	10	15 : 1 at all phase angles	50	no device degradation

[1] $t_p = 100\text{ }\mu\text{s}$; $\delta = 10\text{ }\%$.

1.2 Features and benefits





- 10 W general purpose broadband RF power GaN HEMT
- High efficiency
- Low thermal resistance
- Excellent ruggedness
- Designed for broadband operation in the frequency range from DC to 6.0 GHz
- 50 V capable 10 W GaN-SiC HEMT in an unmatched configuration in an air-cavity ceramic package
- Offers agile performance in an easy to apply package
- For RoHS compliance see the product details on the Ampleon website
- Large signal models in ADS and MWO are available on the Ampleon website

1.3 Applications

- Broadband tactical communication
- Broadband countermeasures
- Instrumentation amplifiers
- Radar for UHF, L- and S-band

2. Pinning information

Table 3. Pinning

Pin	Description	Simplified outline	Graphic symbol
CLF3H0060-10 (SOT1227A)			
1	drain		 amp01464
2	gate		
3	source		
CLF3H0060S-10 (SOT1227B)			
1	drain		 amp01464
2	gate		
3	source		

[1] Connected to flange.

3. Ordering information

Table 4. Ordering information

Package name	Orderable part number	12NC	Packing description	Min. orderable quantity (pieces)
SOT1227A	CLF3H0060-10U	9349 606 01112	Tray; 20-fold; non-dry pack	60
SOT1227B	CLF3H0060S-10U	9349 606 02112	Tray; 20-fold; non-dry pack	60

4. Limiting values

Table 5. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	drain-source voltage		-	150	V
V_{GS}	gate-source voltage		-8	+2	V
I_{GF}	forward gate current	external $R_G = 5 \Omega$	-	4.4	mA
T_{stg}	storage temperature		-65	+150	°C
T_{ch}	active die channel temperature		[1]	300	°C

[1] Continuous use at maximum temperature will affect the reliability, for details refer to the online MTF calculator.

5. Thermal characteristics

Table 6. Thermal characteristics

Symbol	Parameter	Conditions	Typ	Unit
$R_{th(s-c)(IR)}$ [1]	thermal resistance from active die surface to case by Infrared measurement	$T_{case} = 85\text{ °C}; V_{DS} = 50\text{ V}; I_{Dq} = 30\text{ mA}; P_{dis} = 7.5\text{ W}$	4.1	K/W
$R_{th(ch-c)(FEA)}$ [2]	thermal resistance from active die channel to case by Finite Element Analysis	$T_{case} = 85\text{ °C}; V_{DS} = 50\text{ V}; I_{Dq} = 30\text{ mA}; P_{dis} = 7.5\text{ W}$	9.0	K/W

[1] Infrared (IR) thermal values are for reference only and cannot be used to determine performance or reliability.

[2] Finite Element Analysis (FEA) thermal values have been used for the online MTF calculator.

6. Characteristics

Table 7. DC characteristics

$T_{case} = 25\text{ °C};$ unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$V_{(BR)DSS}$	drain-source breakdown voltage	$V_{GS} = -8\text{ V}; I_D = 2\text{ mA}$	150	-	-	V
$V_{GS(th)}$	gate-source threshold voltage	$V_{DS} = 6\text{ V}; I_D = 2\text{ mA}$	-3.5	-2.7	-2.2	V
I_{DSX}	drain cut-off current	$V_{GS} = 2\text{ V}; V_{DS} = 6\text{ V}$	-	1.57	-	A
I_{GSS}	gate leakage current	$V_{GS} = -8\text{ V}; V_{DS} = 10\text{ V}$	-	-	120	μA
g_{fs}	forward transconductance	$V_{GS} = 0\text{ V}; V_{DS} = 6\text{ V}$	-	0.44	-	S
$R_{DS(on)}$	drain-source on-state resistance	$V_{GS} = 0\text{ V}; V_{DS} = 100\text{ mV}$	-	2.0	-	Ω

Table 8. AC characteristics

$T_j = 25\text{ °C};$ unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
C_{iss}	input capacitance	$V_{GS} = -8\text{ V}; V_{DS} = 50\text{ V}; f = 1\text{ MHz}$ [1]	-	2.92	-	pF
C_{oss}	output capacitance	$V_{GS} = -8\text{ V}; V_{DS} = 50\text{ V}; f = 1\text{ MHz}$ [1]	-	1.78	-	pF
C_{rss}	reverse transfer capacitance	$V_{GS} = -8\text{ V}; V_{DS} = 50\text{ V}; f = 1\text{ MHz}$ [1]	-	0.25	-	pF

[1] Include package.

Table 9. RF characteristics

Test signal: pulsed CW; $t_p = 100\text{ }\mu\text{s}; \delta = 10\text{ %}; V_{DS} = 50\text{ V}; I_{Dq} = 30\text{ mA}; T_{case} = 25\text{ °C};$ unless otherwise specified; in a class-AB production circuit measured at 2500 MHz.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
G_p	power gain	$P_L = 10\text{ W}$	18.8	20.1	-	dB
RL_{in}	input return loss	$P_L = 10\text{ W}$	-	-15	-	dB
η_D	drain efficiency	$P_L = 10\text{ W}$	57	63	-	%

7. Application information

7.1 Production circuit information (f = 2500 MHz)





Table 10. List of components


For test circuit see [Figure 1](#).

Component	Description	Value	Remarks
C1	multilayer ceramic chip capacitor	8.2 pF	ATC 100A
C2	multilayer ceramic chip capacitor	33 pF	ATC 100A
C3	multilayer ceramic chip capacitor	56 pF	ATC 100A
C4	multilayer ceramic chip capacitor	51 pF	ATC 100A
C5	multilayer ceramic chip capacitor	20 pF	ATC 100A
C6	multilayer ceramic chip capacitor	15 pF	ATC 100A
C7, C10	multilayer ceramic chip capacitor	22 pF	ATC 100A
C8, C11	multilayer ceramic chip capacitor	0.1 μF	GRM21BR71H104KA01L
C9, C12	multilayer ceramic chip capacitor	1 μF	GRM32RR71H105KA01L
C13	electrolytic capacitor	1000 μF, 63 V	
R1	resistor	10 Ω	0805
R2	shunt resistor	100 mΩ	CRA2512 R100E

7.2 Graphical data (f = 200 MHz to 3200 MHz)

7.2.1 CW performance (V_{DS} = 40 V)






$V_{DS} = 40\text{ V}; I_{Dq} = 40\text{ mA}$.

- (1) f = 200 MHz
- (2) f = 500 MHz
- (3) f = 1000 MHz
- (4) f = 1500 MHz
- (5) f = 2000 MHz
- (6) f = 2400 MHz
- (7) f = 2800 MHz
- (8) f = 3200 MHz

Fig 4. Drain efficiency as a function of output power; typical values





$V_{DS} = 40\text{ V}; I_{Dq} = 40\text{ mA}$.

- (1) f = 200 MHz
- (2) f = 500 MHz
- (3) f = 1000 MHz
- (4) f = 1500 MHz
- (5) f = 2000 MHz
- (6) f = 2400 MHz
- (7) f = 2800 MHz
- (8) f = 3200 MHz

Fig 5. Output power as a function of input power; typical values

7.2.2 Pulsed CW performance ($V_{DS} = 50\text{ V}$)





8. Test information

8.1 Load-pull impedance information

The measured load-pull impedances are shown below. Impedance reference plane defined at device leads. Measurements performed with Ampleon test fixtures. Test temperature set at 25 °C with a pulsed CW signal; $t_p = 100 \mu\text{s}; \delta = 10 \%$; RF performance at $V_{DS} = 50 \text{ V}; I_{Dq} = 30 \text{ mA}$.

Table 11. Typical impedance
Typical values unless otherwise specified.

f (MHz)	Z _S (Ω)	Z _L (maximum P _{L(M)}) (Ω)	Z _L (maximum η _D) (Ω)
1000	3.2 + j28.7	46 + j10	67 + j86
2000	3.2 + j7.3	30 + j24	18 + j41
3000	3.1 - j2.4	16 + j19	11 + j25
5000	6.9 - j22.0	13 + j2.2	8.7 + j4.0
6000	18.1 - j39.2	13 - j2.6	7.1 - j5.2

[1] Z_S and Z_L defined in [Figure 10](#).




Fig 10. Definition of transistor impedance

Z_S is the measured source pull impedance presented to the device. Z_L is the measured load pull impedance presented to the device.

9. Package outline

Flanged ceramic package; 2 mounting holes; 2 leads

SOT1227A




Fig 11. Package outline SOT1227A

Earless Flanged ceramic package; 2 leads

SOT1227B




Fig 12. Package outline SOT1227B

10. Handling information

CAUTION



This device is sensitive to ElectroStatic Discharge (ESD). Observe precautions for handling electrostatic sensitive devices.

Such precautions are described in the *ANSI/ESD S20.20*, *IEC/ST 61340-5*, *JESD625-A* or equivalent standards.

Table 12. ESD sensitivity

ESD model	Class
Charged Device Model (CDM); According to ANSI/ESDA/JEDEC standard JS-002	C2A [1]
Human Body Model (HBM); According to ANSI/ESDA/JEDEC standard JS-001	0B [2]

[1] CDM classification C2A is granted to any part that passes after exposure to an ESD pulse of 500 V.

[2] HBM classification 0B is granted to any part that passes after exposure to an ESD pulse of 125 V.

11. Abbreviations

Table 13. Abbreviations

Acronym	Description
ADS	Advanced Design System
CW	Continuous Wave
ESD	ElectroStatic Discharge
GaN	Gallium Nitride
HEMT	High Electron Mobility Transistor
L-band	Long wave band
MTF	Median Time to Failure
MWO	Microwave Office
RoHS	Restriction of Hazardous Substances
S-band	Short wave band
SiC	Silicon Carbide
UHF	Ultra High Frequency
VSWR	Voltage Standing Wave Ratio

12. Revision history

Table 14. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
CLF3H0060-10_3H0060S-10 v.1	20230717	Product data sheet	-	-

13. Legal information

13.1 Data sheet status

Document status ^{[1][2]}	Product status ^[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.ampleon.com>.

13.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Ampleon does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Ampleon sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Ampleon and its customer, unless Ampleon and customer have explicitly agreed otherwise in writing. An agreement according to which the functions and qualities of Ampleon products exceed those described in the Product data sheet is invalid.

Right to make changes — Ampleon reserves the right to change information including but without limitation specifications and product descriptions published in this document at any time and without notice. This document supersedes and replaces all information regarding these products supplied prior to the publication hereof.

Suitability for use — Ampleon products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an Ampleon product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Insofar as a customer or another party nevertheless uses Ampleon products unlawfully for such purposes, Ampleon and its suppliers are not liable for any damages.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Ampleon makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Ampleon products, and Ampleon is not liable for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Ampleon product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers shall provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Ampleon is not liable related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for and shall do all necessary testing for the customer's applications and products using Ampleon products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Ampleon is not liable in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not guaranteed. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — Ampleon products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.ampleon.com/terms>, unless otherwise agreed in a valid written individual agreement. In the event of signing an individual agreement the terms and conditions of the respective agreement shall apply. Ampleon hereby expressly objects to and rejects the validity of customer's terms and conditions regarding the purchase of Ampleon products by customer.

13.3 Disclaimers

Maturity — After the relevant product(s) have passed the Release Gate in Ampleon's release process, Ampleon will confirm the final version in writing.

Limited warranty and liability — Ampleon uses its best efforts to keep the information in this document accurate and reliable. However, Ampleon gives no representations or warranties, expressed or implied, as to the accuracy or completeness of such information and assumes no liability for the consequences of the use of such information. Ampleon is not liable for content provided by an external information source.

In no event and irrespective of the legal basis (contract, tort (including negligence) statutory liability, misrepresentation, indemnity or any other area of law) shall Ampleon be liable for any indirect, incidental, punitive, special or consequential damages (including but without limitation loss of profit or revenue, loss of use or loss of production, loss of data, cost of capital, cost of substitute goods, property damage external to the Ampleon products and any damage, expenditure or loss arising out of such damage, business interruption, costs related to the removal or replacement of any products or rework charges) or any of the foregoing suffered by any third party.

Notwithstanding any damages that customer might incur for any reason whatsoever, Ampleon's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Ampleon.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Non-automotive qualified products — Unless this data sheet expressly states that this specific Ampleon product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Ampleon is not liable for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer breaches this and uses the products for design and use in automotive applications in accordance with automotive specifications and standards, (a) Ampleon gives no warranty, representation

or other guarantees of any kind with respect to such automotive applications, use and specifications, and (b) such use is solely and exclusively at customer's own risk, and (c) customer fully indemnifies Ampleon against any and all liability, damages or failed product claims, including against third parties, arising out of customer's design and use of the product for automotive applications.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

13.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

14. Contact information

For more information, please visit: <http://www.ampleon.com>

For sales office addresses, please visit: <http://www.ampleon.com/sales>

15. Contents

1 **Product profile** 1

1.1 General description 1

1.2 Features and benefits 1

1.3 Applications 1

2 **Pinning information** 2

3 **Ordering information** 2

4 **Limiting values** 2

5 **Thermal characteristics** 3

6 **Characteristics** 3

7 **Application information** 4

7.1 Production circuit information (f = 2500 MHz) 4

7.2 Graphical data (f = 200 MHz to 3200 MHz) 5

7.2.1 CW performance (V_{DS} = 40 V) 5

7.2.2 Pulsed CW performance (V_{DS} = 50 V) 7

8 **Test information** 8

8.1 Load-pull impedance information 8

9 **Package outline** 10

10 **Handling information** 12

11 **Abbreviations** 12

12 **Revision history** 12

13 **Legal information** 13

13.1 Data sheet status 13

13.2 Definitions 13

13.3 Disclaimers 13

13.4 Trademarks 14

14 **Contact information** 14

15 **Contents** 15

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© Ampleon Netherlands B.V. 2023. All rights reserved.

For more information, please visit: <http://www.ampleon.com>
 For sales office addresses, please visit: <http://www.ampleon.com/sales>

Date of release: 17 July 2023

Document identifier: CLF3H0060-10_3H0060S-10