

Transfer Electromechanical Relay Latching Switch, +COM, DC to 52 GHz, 5W, 12VDC, 2.4mm

The FMSW6581 is a Transfer electromechanical relay switch that operates across an ultra wideband frequency range from DC to 52 GHz and can handle 5W of average power in a break before make condition. The 50 Ohm design supports a positive common (+COM) biasing configuration and features a Latching Actuator with a 1 million lifecycle rating. The Latching Actuator magnetically latches in place after the control voltage is removed. For power sensitive applications, this is the best actuator option. Impressive typical performance includes 1.2 dB insertion loss and isolation greater than 70 dB. This switch requires 12 Vdc bias voltage and operates over a temperature range of -25°C to +65°C. The rugged and compact package assembly supports 2.4mm female connectors and solder terminal pins for DC control. And for highly reliable operation, the model is guaranteed to meet MIL-STD-202 environmental test conditions for shock and random vibration.

Electrical Specifications (TA = +25°C, DC Voltage = 12 Vdc)

Switch Type
Actuator Type

Transfer
Latching

Description	Min	Typ	Max	Units
Frequency Range	DC		52	GHz
Operating Voltage	11	12	13	Volts
Actuating Current @ 12 Volts		300		mA
VSWR		1.9:1	2.8:1	
Insertion Loss		1.2	2.3	dB
Isolation	50	80		dB
Switching Time		20		ms

Performance by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC - 6	6 - 12.4	12.4 - 18	18 - 26.5	26.5 - 40	GHz
VSWR, Max	1.3:1	1.4:1	1.5:1	1.7:1	1.9:1	
Insertion Loss, Max	0.3	0.4	0.5	0.7	1	dB
Isolation, Min	70	60	60	55	50	dB

Performance by Frequency

Description	F6	F7	F8	F9	F10	Units
Frequency Range	40 - 50	50 - 52				GHz
VSWR, Max	2.2:12.8:1					
Insertion Loss, Max	1.3	2.3				dB
Isolation, Min	50	50				dB



Features:

- Transfer Electromechanical Relay Switch
- DC to 52 GHz Frequency Range
- Latching Actuator
- Positive Common (+COM) Configuration
- 1M Lifecycle Rating
- Insertion Loss 1.2 dB typ
- Isolation > 70 dB typ
- VSWR as low as 1.3:1 max
- Solder Terminal Pins for DC Control
- 12 Volt DC Bias
- 2.4mm Female Connectors
- -25°C to +65°C Operating Temperature
- 5 Watt Average Power Handling
- 50 Ohm Design
- Hot Switching Capability - Consult Factory
- S-Parameter Data available upon request
- Rugged Design meets Mil-STD-202 Test Conditions

Applications:

- Aerospace & Defense
- Test & Measurement
- Microwave Radio Systems
- Military & Commercial Communication Systems
- Research & Development
- SATCOM
- Wireless Communications
- Enterprise
- IoT

Fairview Microwave
301 Leora Ln., Suite 100
Lewisville, TX 75056
Tel: 1-800-715-4396 / (972) 649-6678
Fax: (972) 649-6689
www.fairviewmicrowave.com
sales@fairviewmicrowave.com

Mechanical Specifications

Size

Length	1.95 in [49.53 mm]
Width/Diameter	2.75 in [69.85 mm]
Height	0.92 in [23.37 mm]
Weight	0.122 lbs [55.34 g]

Connectors

RF Connector Type	2.4mm Female
Control Connector	Solder Terminals

Environmental Specifications

Temperature

Operating Range	-25 to +65 deg C
Storage Range	-55 to +100 deg C


Shock	MIL-STD-202 Method 213, Condition D, 500G (non oper)
Vibration	MIL-STD-202 Method 204, Condition D, 10G RMS (non oper)



Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:


Typical Performance Data





Power Handling vs. Frequency

Power Handling vs. Frequency



Power handling chart and derating curves based on the following conditions:

- Ambient temperature: 40°C or less
- Altitude: Sea level
- Load VSWR: 1.20:1 Maximum
- Relative Humidity: 40-50%
- Cold switching: RF signal off

Note: specifications subject to change without notice

Transfer Electromechanical Relay Latching Switch, +COM, DC to 52 GHz, 5W, 12VDC, 2.4mm from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [Transfer Electromechanical Relay Latching Switch, +COM, DC to 52 GHz, 5W, 12VDC, 2.4mm FMSW6581](#)

URL: <https://www.fairviewmicrowave.com/transfer-latching-52-ghz-electro-mechanical-relay-switch-12v-2.4mm-fm-sw6581-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.

