



Transfer Electromechanical Relay Failsafe Switch
DC to 40 GHz, 2M Lifecycles, 2.92mm, 5 Watts,
28V, Indicators, TTL, Diodes, Solder Pins

Electromechanical Relay Switches Technical Data Sheet

PE71S6482

Features

- Transfer Electromechanical Relay Switch
- DC to 40 GHz Frequency Range
- Failsafe Actuator
- TTL Logic Control
- Suppression Diodes
- Indicators
- 2M Lifecycle Rating
- Insertion Loss 0.5 dB typ
- Isolation > 85 dB typ
- VSWR as low as 1.2:1 max
- +28 Volt DC Bias
- Solder Terminal Pins for all Command Control Functions
- 2.92mm Female Connectors
- -25°C to +65°C Operating Temperature
- Up to 5 Watt Average Power Handling
- 50 Ohm Design
- Hot Switching Capability - Consult Factory
- S-Parameter Data available upon request
- Rugged Design meets Mil-STD-202 Test Conditions

Applications

- Aerospace & Defense
- Test & Measurement
- Microwave Radio Systems
- Military & Commercial Communication Systems
- Research & Development
- SATCOM
- Wireless Communications
- Enterprise
- IoT

Description

The PE71S6482 is a Transfer electromechanical relay switch that operates across a wide frequency range from DC to 40 GHz and can handle up to 5 Watts of average power in a break before make condition. The 50 Ohm design is rated for 2 million lifecycles and features a Failsafe Actuator. Additional features include TTL logic control, suppression diodes which limit voltage spikes or reverse current, and Indicators to monitor the switch position. Impressive typical performance includes 0.5 dB insertion loss and isolation greater than 85 dB. This switch requires +28Vdc bias voltage and operates over a temperature range of -25°C to +65°C. The rugged and compact package assembly supports 2.92mm female connectors and solder terminal pins for DC command control functions. And for highly reliable operation, the model is guaranteed to meet MIL-STD-202 environmental test conditions for shock and random vibration.

Electrical Specifications (TA = +25°C, DC Voltage = +28 Vdc)

Switch Type	Transfer
Actuator Type	Failsafe
Actuator Options	Indicators, TTL Logic
TTL Control	on: 2.4 to 5.5 Volts off: 0 to 0.8 Volts

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		40	GHz
Operating Voltage		+28		Volts
Actuating Set Current @ +28 Volts			160	mA
VSWR		1.4:1	1.8:1	
Insertion Loss		0.5	1	dB
Isolation	50	85		dB

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Transfer Electromechanical Relay Failsafe Switch DC to 40 GHz, 2M Lifecycles, 2.92mm, 5 Watts, 28V, Indicators, TTL, Diodes, Solder Pins PE71S6482](#)



Transfer Electromechanical Relay Failsafe Switch
DC to 40 GHz, 2M Lifecycles, 2.92mm, 5 Watts,
28V, Indicators, TTL, Diodes, Solder Pins

Electromechanical Relay Switches Technical Data

PE71S6482

Input Power (CW) 5 Watts
(at 40 GHz)

Performance by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC to 6	6 to 12.4	12.4 to 26.5	26.5 to 40		GHz
VSWR, Max	1.2:1	1.3:1	1.4:1	1.8:1		
Insertion Loss, Max	0.2	0.4	0.7	1		dB
Isolation, Min	85	80	65	50		dB

Mechanical Specifications

Size

Length 2 in [50.8 mm]
Width/Diameter 2.16 in [54.86 mm]
Height 1.26 in [32 mm]
Weight 0.1 lbs [45.36 g]

Connectors

RF Connector Type 2.92mm Female

Environmental Specifications

Temperature

Operating Range -25 to +65 deg C
Storage Range -55 to +100 deg C

Shock

MIL-STD-202 Method 213, Condition D, 500G (non oper)

Vibration

MIL-STD-202 Method 204, Condition D, 10G RMS (non oper)

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Transfer Electromechanical Relay Failsafe Switch DC to 40 GHz, 2M Lifecycles, 2.92mm, 5 Watts, 28V, Indicators, TTL, Diodes, Solder Pins PE71S6482](#)




Transfer Electromechanical Relay Failsafe Switch
DC to 40 GHz, 2M Lifecycles, 2.92mm, 5 Watts,
28V, Indicators, TTL, Diodes, Solder Pins

Electromechanical Relay Switches Technical Data

PE71S6482

Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Transfer Electromechanical Relay Failsafe Switch DC to 40 GHz, 2M Lifecycles, 2.92mm, 5 Watts, 28V, Indicators, TTL, Diodes, Solder Pins PE71S6482](#)



Transfer Electromechanical Relay Failsafe Switch
DC to 40 GHz, 2M Lifecycles, 2.92mm, 5 Watts,
28V, Indicators, TTL, Diodes, Solder Pins

Electromechanical Relay Switches Technical Data

PE71S6482





Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Transfer Electromechanical Relay Failsafe Switch DC to 40 GHz, 2M Lifecycles, 2.92mm, 5 Watts, 28V, Indicators, TTL, Diodes, Solder Pins PE71S6482](#)



Transfer Electromechanical Relay Failsafe Switch
DC to 40 GHz, 2M Lifecycles, 2.92mm, 5 Watts,
28V, Indicators, TTL, Diodes, Solder Pins

Electromechanical Relay Switches Technical Data

PE71S6482



Power Handling Chart and Derating Curves based on the following Test and Environmental Conditions:
Ambient temperature: 20-25°C
Altitude: Sea Level to 1,000 feet
Relative Humidity: 50-55%
Load VSWR: ≤ 1.20:1
Operation: Cold Switching

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Transfer Electromechanical Relay Failsafe Switch DC to 40 GHz, 2M Lifecycles, 2.92mm, 5 Watts, 28V, Indicators, TTL, Diodes, Solder Pins PE71S6482](#)



Transfer Electromechanical Relay Failsafe Switch
DC to 40 GHz, 2M Lifecycles, 2.92mm, 5 Watts,
28V, Indicators, TTL, Diodes, Solder Pins

Electromechanical Relay Switches Technical Data

PE71S6482

Transfer Electromechanical Relay Failsafe Switch DC to 40 GHz, 2M Lifecycles, 2.92mm, 5 Watts, 28V, Indicators, TTL, Diodes, Solder Pins from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Transfer Electromechanical Relay Failsafe Switch DC to 40 GHz, 2M Lifecycles, 2.92mm, 5 Watts, 28V, Indicators, TTL, Diodes, Solder Pins PE71S6482](https://www.pasternack.com/transfer-electromechanical-relay-failsafe-switch-40-ghz-5w-28v-indicators-ttl-2.92mm-pe71s6482-p.aspx)

URL: <https://www.pasternack.com/transfer-electromechanical-relay-failsafe-switch-40-ghz-5w-28v-indicators-ttl-2.92mm-pe71s6482-p.aspx>


The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE71S6482 CAD Drawing

Transfer Electromechanical Relay Failsafe Switch DC to 40 GHz, 2M
Lifecycles, 2.92mm, 5 Watts, 28V, Indicators, TTL, Diodes, Solder Pins

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	05/17/2022	T. GALLA

6X SOLDER TERMINALS,
SOLDER WIRE USING SN96,
MAXIMUM TEMP 250 °C FOR
NO MORE THAN 5 SEC.



NOTES:

1. LABEL PER ILS-100-02. FOR INTERNAL REFERENCE ONLY.
LABEL LOCATION FOR REFERENCE ONLY.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

.X = ± .2 [5.08]
.XX = ± .02 [.51]
.XXX = ± .005 [.13]
ANGLES ± 1°

CABLE LENGTH (L) TOLERANCES:

L ≤ 12 [305] = ±1 [25] / -0
12 [305] < L ≤ 60 [1524] = +2 [51] / -0
60 [1524] < L ≤ 120 [3048] = +4 [102] / -0
120 [3048] < L ≤ 300 [7620] = +6 [152] / -0
300 [7620] < L = +5%L / -0

ALL DIMENSIONS SHOWN
ARE FOR REFERENCE ONLY.

THIRD-ANGLE PROJECTION

THE INFORMATION AND
DESIGN IN THIS DOCUMENT
IS THE PROPERTY OF
PASTERNAK CORPORATION
ALL RIGHTS RESERVED.

SHEET 1 OF 2

SCALE N/A

REV A


PE PASTERNAK
an INFINITI brand

Pasternack Enterprises, Inc.
P.O. Box 16759, Irvine, CA 92623.
Phone: 1.949.261.1920 | 1.866.727.8376
Fax: 1.949.261.7451
Website: www.pasternack.com
E-mail: sales@pasternack.com

SIZE A CAGE CODE 53919 DRAWN BY KGLEBOVA ITEM NO. PE71S6482 REV A

PE71S6482 CAD Drawing

Transfer Electromechanical Relay Failsafe Switch DC to 40 GHz, 2M
Lifecycles, 2.92mm, 5 Watts, 28V, Indicators, TTL, Diodes, Solder Pins



TTL LOGIC	RF PATH	INDICATOR PATH
PIN 1		
OFF	J1-J2, J3-J4	A-C
ON	J1-J3, J2-J4	B-C

SCHEMATIC

UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

.X = ± .2	[.08]	FRACTIONS
.XX = ± .02	[.51]	± 1/32
.XXX = ± .005	[.13]	ANGLES ± 1°

CABLE LENGTH (L) TOLERANCES:

L ≤ 12	[305]	= +1 [25] / -0
12 [305] < L ≤ 60	[1524]	= +2 [51] / -0
60 [1524] < L ≤ 120	[3048]	= +4 [102] / -0
120 [3048] < L ≤ 300	[7620]	= +6 [152] / -0
300 [7620] < L		= +5%L / -0

ALL DIMENSIONS SHOWN
ARE FOR REFERENCE ONLY.

PE PASTERNAK
an INFINITE brand

Pasternack Enterprises, Inc.
P.O. Box 16759, Irvine, CA 92623.
Phone: 1.949.261.1920 | 1.866.727.8376
Fax: 1.949.261.7451
Website: www.pasternack.com
E-mail: sales@pasternack.com

THIRD-ANGLE PROJECTION

THE INFORMATION AND
DESIGN IN THIS DOCUMENT
IS THE PROPERTY OF
PASTERNAK CORPORATION
ALL RIGHTS RESERVED.

SHEET	2	OF	2
SCALE	N/A		
REV	A		

SIZE	CAGE CODE	DRAWN BY	ITEM NO.
A	53919	KGLEBOVA	PE71S6482

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE
WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.