



TE Internal #: 440423-1
C-Clip PCB Spring Contact, Uncompressed Height 5 mm [.197 in],
Length 7 mm [.276 in], Width 2.5 mm [.098 in], 3.5 mm [.138 in]
Working Range (Low)
[View on TE.com >](#)

Connectors > Contacts > PCB Spring Contacts



Spring Finger Type: **C-Clip**
Scalable: **No**
Side Protected: **No**
Uncompressed Height: **5 mm [.197 in]**
Product Length: **7 mm [.276 in]**

Features

Product Type Features

Connector System	Board-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Spring Finger Type	C-Clip
Scalable	No

Configuration Features

Number of Positions	1
Side Protected	No

Contact Features

Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Gold
Contact Base Material	Copper Alloy
Contact Working Range (Low)	3.5 mm[.138 in]
Contact Working Range (High)	4.25 mm[.167 in]
Point of Contact Area Plating Material	Gold
Contact Current Rating (Max)	1 A

Dimensions

Uncompressed Height	5 mm[.197 in]
Product Length	7 mm[.276 in]



Product Width	2.5 mm[.098 in]
---------------	-----------------

Usage Conditions

Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
-----------------------------	---------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Packaging Features

Packaging Quantity	1500
Packaging Method	Tape & Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1447009-8
SHIELD FINGER 3525Z

TE Part # 1734298-1
Shield Finger 6525

Customers Also Bought

TE Part # 8-188275-0
MICRO-MATCH SMD FTE

TE Part # 50462-6
SOCKET,MIN-SPR AU SER-2

TE Part # 1393243-4
RTE24012

TE Part # 9-1625892-1
3W SM M/OX 5% 120K

TE Part # 2339640-1
SPRING FINGER 6025

TE Part # 1565749-4
Signal Header

TE Part # GA30K5A316I
DISC-DISCRETE

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_440423-1_O.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_440423-1_O.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_440423-1_O.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages

Products for Mobile Equipment

English

440423-1

C-Clip PCB Spring Contact, Uncompressed Height 5 mm [.197 in], Length 7 mm [.276 in], Width 2.5 mm [.098 in], 3.5 mm [.138 in] Working Range (Low)



Product Specifications

Product Specification

English