

M4(200)-240X30M

Aliases (UFSM40020DT000)

KEMET, M4, Flex Suppressors, RFID

	W	Т

General Information				
Series	M4			
Style	Sheet			
Description	Flex Suppressor Halogen Free Type			
Features	High Magnetic Permeability Type, Low Magnetic Loss Type			
RoHS	Yes			
Qualifications	UL94 HB, UL File No. E176124			
Environment	Halogen Free, PVC Free, Lead Free, Red Phosphorus Free			

Specifications		
Temperature Range	-40/+105°C	
Permeability	40 u At 13.56MHz	
Effective Frequency	13.56 MHz and below	
Specific Gravity	3.1TYP	
Surface Resistivity	10 MOhm/sq. TYP	

Dimensions		
Sheet Size	240mmx30M	
L	30000mm NOM	
W	240mm NOM	
T	0.2mm NOM	

Packaging Specifications		
Tape Description	No Adhesive Tape	
Typical Component Weight	4176.25 g	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.