

SACB-8/16-M23 P12 SH - Distributor box



1155996

<https://www.phoenixcontact.com/us/products/1155996>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Distributor box, application: Standard, connection method: M12 socket Metal, number of slots: 8, number of positions: 5, coding: A, slot assignment: Double, status display: No, Universal; master cable connection: M23 plug connection 180°, shielding: yes

Your advantages

- Safety in the field, thanks to molded housing and high degree of protection
- Save space: distributor box with double occupancy for two sensors in one slot
- Reliable signal transmission – 360° shielding in environments with electromagnetic interference

Commercial data

Item number	1155996
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF43
Product key	BF3CDB
GTIN	4063151158835
Weight per piece (including packing)	603.5 g
Weight per piece (excluding packing)	554 g
Customs tariff number	85366990
Country of origin	DE

SACB-8/16-M23 P12 SH - Distributor box



1155996

<https://www.phoenixcontact.com/us/products/1155996>

Technical data

Notes

Note on application	Not suitable for M12 push-pull connectors.
Assembly note	NOTE: Observe the permissible bending radii when laying conductors, since the degree of protection may be put in jeopardy if the bending forces are too high. Alleviate mechanical loads upstream of the connector, e.g. by using cable ties.
Note on application	Unused slots are to be sealed off prior to commissioning. Suitable sealing elements are to be found under "Accessories".

Product properties

Product type	Distributor box
Application	Standard
Number of positions	5
Number of slots	8
Coding	A

Electrical properties

Nominal voltage U_N	48 V AC
	60 V DC
Rated current, total	10 A (up to 40 °C)
Max. current carrying capacity per path	2 A
Current carrying capacity per slot	4 A

Connection data

Conductor connection

Sensor/actuator connection system	M12 socket
Tightening torque slot sensor/actuator cable	0.4 Nm

Pin assignment

Slot/position = Wire color or connection	1 / 4 (A) = 15
	1 / 2 (B) = 7
	2 / 4 (A) = 5
	2 / 2 (B) = 4
	3 / 4 (A) = 16
	3 / 2 (B) = 8
	4 / 4 (A) = 3
	4 / 2 (B) = 14
	5 / 4 (A) = 17
	5 / 2 (B) = 9
	6 / 4 (A) = 2
	6 / 2 (B) = 13
	7 / 4 (A) = 11

SACB-8/16-M23 P12 SH - Distributor box



1155996

<https://www.phoenixcontact.com/us/products/1155996>


$7 / 2 (B) = 10$
$8 / 4 (A) = 1$
$8 / 2 (B) = 18$
$1-8 / 1 (+ 48 V) = 19$
$1-8 / 3 (0 V) = 6$
$1-8 / 5 (PE) = 12$

Signaling

Status display present	No
------------------------	----

Dimensions

Dimensional drawing



Width	58 mm
Height	36 mm
Length	160 mm

Material specifications

Material Threaded sleeve	Die-cast zinc
Material Housing	Die-cast zinc
Material Molding compound	PUR
Flammability rating according to UL 94	V0
Seal material O-ring	FKM
Contact material	Cu alloy
Contact surface material	gold-plated
Contact carrier material	PA
Material of contact, master cable side	CU alloy
Material of the contact carrier on the master cable side	PBT
Material of contact surface, master cable side	gold-plated

Cable/line

Connection method	M23 plug connection
-------------------	---------------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-25 °C ... 70 °C

Standards and regulations

SACB-8/16-M23 P12 SH - Distributor box



1155996


<https://www.phoenixcontact.com/us/products/1155996>

M12

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101


Drawings

Schematic diagram



M23 plug connection pin, 19-pos.

Schematic diagram




M12 slot, socket, 5-pos.

SACB-8/16-M23 P12 SH - Distributor box



1155996

<https://www.phoenixcontact.com/us/products/1155996>




SACB-8/16-M23 P12 SH - Distributor box



1155996

<https://www.phoenixcontact.com/us/products/1155996>

Circuit diagram



SACB-8/16-M23 P12 SH - Distributor box



1155996

<https://www.phoenixcontact.com/us/products/1155996>

Classifications

ECLASS

ECLASS-11.0	27440111
ECLASS-12.0	27440111
ECLASS-13.0	27440111

ETIM

ETIM 9.0	EC003558
----------	----------

UNSPSC

UNSPSC 21.0	31251500
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(a)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	4f91e7b3-4fb4-40fa-940b-2eecd8c39f4f

SACB-8/16-M23 P12 SH - Distributor box



1155996

<https://www.phoenixcontact.com/us/products/1155996>

Accessories

PROT M12 MS PWR - Screw plug

1092802

<https://www.phoenixcontact.com/us/products/1092802>



An M12 screw plug for the unoccupied M12 females of the M12 POWER connectors, boxes, and flush-type connectors

UC-EM (17,5X9) - Snap-in markers

0827490

<https://www.phoenixcontact.com/us/products/0827490>



Snap-in markers, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID, BLUEMARK ID COLOR, BLUEMARK CLED, BLUEMARK LED, CMS-P1-PLOTTER, PLOTMARK, mounting type: snapped, lettering field size: 17.5 x 9 mm, Number of individual labels: 20

SACB-8/16-M23 P12 SH - Distributor box



1155996

<https://www.phoenixcontact.com/us/products/1155996>

UC-EM (17,5X9) CUS - Snap-in markers

0828238

<https://www.phoenixcontact.com/us/products/0828238>

Snap-in markers, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snapped into marker carrier, lettering field size: 17.5 x 9 mm, Number of individual labels: 20



UCT-EM (17,5X9) - Snap-in markers

0801491

<https://www.phoenixcontact.com/us/products/0801491>

Snap-in markers, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, lettering field size: 17.5 x 9 mm, Number of individual labels: 24



SACB-8/16-M23 P12 SH - Distributor box



1155996

<https://www.phoenixcontact.com/us/products/1155996>

UCT-EM (17,5X9) CUS - Snap-in markers

0801575

<https://www.phoenixcontact.com/us/products/0801575>

UniCard sheet, for labeling devices from other manufacturers, for overview table see download area, labeled according to customer specifications




UC-EM (17,5X9) YE - Snap-in markers

0827494

<https://www.phoenixcontact.com/us/products/0827494>

Snap-in markers, Sheet, yellow, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, lettering field size: 17.5 x 9 mm, Number of individual labels: 20



SACB-8/16-M23 P12 SH - Distributor box




1155996

<https://www.phoenixcontact.com/us/products/1155996>

UC-EM (17,5X9) YE CUS - Snap-in markers

0828239

<https://www.phoenixcontact.com/us/products/0828239>



Snap-in markers, can be ordered: by sheet, yellow, labeled according to customer specifications, mounting type: snapped into marker carrier, lettering field size: 17.5 x 9 mm, Number of individual labels: 20

UCT-EM (17,5X9) YE - Snap-in markers

0801492

<https://www.phoenixcontact.com/us/products/0801492>



Snap-in markers, Sheet, yellow, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, lettering field size: 17.5 x 9 mm, Number of individual labels: 24

SACB-8/16-M23 P12 SH - Distributor box

1155996

<https://www.phoenixcontact.com/us/products/1155996>



UCT-EM (17,5X9) YE CUS - Snap-in markers

0801576

<https://www.phoenixcontact.com/us/products/0801576>

UniCard sheet, for labeling devices from other manufacturers, for overview table see download area, labeled according to customer specifications



RCK-TWGM/BL16+3/ 5,0PUR SH - Master cable

1519529

<https://www.phoenixcontact.com/us/products/1519529>



Master cable, application: Sensor/actuator box, connection method: M12 socket Metal, number of positions: 19, slot assignment: Double, status display: No; master cable connection: M23 plug connection, PUR/PVC, cable length: 5 m, shielding: yes, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1260760

SACB-8/16-M23 P12 SH - Distributor box



1155996

<https://www.phoenixcontact.com/us/products/1155996>

RCK-TWGM/BL16+3/10,0PUR SH - Master cable

1511828

<https://www.phoenixcontact.com/us/products/1511828>



Master cable, application: Sensor/actuator box, connection method: M12 socket Metal, number of positions: 19, slot assignment: Double, status display: No; master cable connection: M23 plug connection, PUR/PVC, cable length: 10 m, shielding: yes, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1260759

RC/TGGM/KVD/LBL 16+3 - Cable connector

1685505

<https://www.phoenixcontact.com/us/products/1685505>



Cable connector, number of positions: 19, status display: No; master cable connection: M23 screw locking, shielding: yes, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1245650

SACB-8/16-M23 P12 SH - Distributor box

1155996

<https://www.phoenixcontact.com/us/products/1155996>



RC/TWGM/KVD/LBL 16+3 - Cable connector

1685518

<https://www.phoenixcontact.com/us/products/1685518>

Cable connector, number of positions: 19, status display: No; master cable connection: M23 screw locking, shielding: yes, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1245651



MSK 1 - Metal protective cap

1665897

<https://www.phoenixcontact.com/us/products/1665897>

Metal protective cap, degree of protection: IP67, when in locked state, color: silver, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1245640



SACB-8/16-M23 P12 SH - Distributor box



1155996

<https://www.phoenixcontact.com/us/products/1155996>

MSK 2 - Protective cap

1665907

<https://www.phoenixcontact.com/us/products/1665907>

Protective cap, degree of protection: IP67, when in locked state, color: silver,
Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.
1 %) item no.: 1245641



KSK 1 - Sealing cap

1685013

<https://www.phoenixcontact.com/us/products/1685013>

Plastic sealing cap, for unoccupied M23 connectors



SACB-8/16-M23 P12 SH - Distributor box

1155996

<https://www.phoenixcontact.com/us/products/1155996>



UTA 136 - DIN rail adapter

2853996

<https://www.phoenixcontact.com/us/products/2853996>

Universal DIN rail adapter, for screwing on switchgear



TSD 04 SAC - Torque screwdriver

1208429

<https://www.phoenixcontact.com/us/products/1208429>

Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors



SACB-8/16-M23 P12 SH - Distributor box



1155996

<https://www.phoenixcontact.com/us/products/1155996>

TSD-M 1,2NM - Torque screwdriver

1212224

<https://www.phoenixcontact.com/us/products/1212224>



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0.3 - 1.2 Nm

TSD-M SAC-BIT ADAPTER - Adapter insert

1212600

<https://www.phoenixcontact.com/us/products/1212600>



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

SACB-8/16-M23 P12 SH - Distributor box

1155996

<https://www.phoenixcontact.com/us/products/1155996>



SAC BIT M12-D15 - Tool

1208432

<https://www.phoenixcontact.com/us/products/1208432>



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a knurl diameter of 15 mm, for 4 mm hexagonal drive

SACC BIT M12-D20 - Tool

1208445

<https://www.phoenixcontact.com/us/products/1208445>



Nut for assembling M12 connectors for assembly with a knurl diameter of 20 mm, for 4 mm hexagonal drive

SACB-8/16-M23 P12 SH - Distributor box

1155996

<https://www.phoenixcontact.com/us/products/1155996>



PLUSCON-RCS - Pipe spanner

1665062

<https://www.phoenixcontact.com/us/products/1665062>



Pipe spanner

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com