



SIMATIC DP, ET 200ECO PN, 8 AI RTD/TC; 8x M12, Degree of protection IP67

Figure similar

General information	
Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	0306H
Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes; against destruction
power supply according to NEC Class 2 required	Yes
Input current	
Current consumption, typ.	110 mA
Power loss	
Power loss, typ.	2.8 W
Analog inputs	
Number of analog inputs	8
<ul style="list-style-type: none"> For resistance/resistance thermometer measurement For thermocouple measurement 	8
<ul style="list-style-type: none"> For thermocouple measurement 	8
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> -80 mV to +80 mV 	Yes
Input ranges (rated values), thermocouples	
<ul style="list-style-type: none"> Type E Type J Type K Type N 	Yes
<ul style="list-style-type: none"> Type E 	Yes
<ul style="list-style-type: none"> Type J 	Yes
<ul style="list-style-type: none"> Type K 	Yes
<ul style="list-style-type: none"> Type N 	Yes
Input ranges (rated values), resistance thermometer	
<ul style="list-style-type: none"> Ni 100 Ni 1000 Ni 120 Ni 200 Ni 500 Pt 100 Pt 1000 Pt 200 Pt 500 	Yes
<ul style="list-style-type: none"> Ni 100 	Yes
<ul style="list-style-type: none"> Ni 1000 	Yes
<ul style="list-style-type: none"> Ni 120 	Yes
<ul style="list-style-type: none"> Ni 200 	Yes
<ul style="list-style-type: none"> Ni 500 	Yes
<ul style="list-style-type: none"> Pt 100 	Yes
<ul style="list-style-type: none"> Pt 1000 	Yes
<ul style="list-style-type: none"> Pt 200 	Yes
<ul style="list-style-type: none"> Pt 500 	Yes
Input ranges (rated values), resistors	
<ul style="list-style-type: none"> 0 to 150 ohms 0 to 300 ohms 0 to 600 ohms 0 to 3000 ohms 	Yes
<ul style="list-style-type: none"> 0 to 150 ohms 	Yes
<ul style="list-style-type: none"> 0 to 300 ohms 	Yes
<ul style="list-style-type: none"> 0 to 600 ohms 	Yes
<ul style="list-style-type: none"> 0 to 3000 ohms 	Yes
Thermocouple (TC)	
Temperature compensation	

— parameterizable	Yes
— internal temperature compensation	Yes
— external temperature compensation with Pt100	Yes
— external temperature compensation with compensations socket	Yes
— dynamic reference temperature value	Yes
— for definable comparison point temperature	Yes
Cable length	
• shielded, max.	30 m
Analog value generation for the inputs	
Analog value display	SIMATIC S7 format
Measurement principle	integrating
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
• Integration time, parameterizable	Yes
• Integration time (ms)	2/16.67/20/100 ms
• Interference voltage suppression for interference frequency f1 in Hz	500 / 60 / 50 / 10 Hz
• Conversion time (per channel)	4 / 19 / 22 / 102 ms
Smoothing of measured values	
• parameterizable	Yes
• Step: None	Yes; 1x cycle time
• Step: low	Yes; 4x cycle time
• Step: Medium	Yes; 16x cycle time
• Step: High	Yes; 64x cycle time
Encoder	
Number of connectable encoders, max.	8
Connection of signal encoders	
• for resistance measurement with two-wire connection	Yes
• for resistance measurement with three-wire connection	Yes
• for resistance measurement with four-wire connection	Yes
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.01 %
Temperature error (relative to input range), (+/-)	RTD: 0.0005%/°C; TC: 0.0035%/°C
Crosstalk between the inputs, min.	-85 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.008 %
Interference voltage suppression for $f = n \times (f1 \pm 1 \%)$, f1 = interference frequency	
• Series mode interference (peak value of interference < rated value of input range), min.	46 dB
• Common mode interference, min.	70 dB
Interfaces	
Transmission procedure	100BASE-TX
Number of PROFINET interfaces	1
1. Interface	
Interface types	
• integrated switch	Yes
Interface types	
M12 port	
• Autonegotiation	Yes
• Autocrossing	Yes
• Transmission rate, max.	100 Mbit/s
Protocols	
Supports protocol for PROFINET IO	Yes
PROFINET CBA	No
PROFIsafe	No
PROFINET IO Device	
Services	
— Prioritized startup	Yes
Redundancy mode	
Media redundancy	

— MRP	Yes
Open IE communication	
• TCP/IP	No
• SNMP	Yes
• DCP	Yes
• LLDP	Yes
• ping	Yes
• ARP	Yes
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnoses	
• Diagnostic information readable	Yes
• Monitoring the supply voltage	Yes; green "ON" LED
• Group error	Yes; Red/yellow "SF/MT" LED
• Overflow/underflow	Yes
Potential separation	
between the load voltages	Yes
between load voltage and all other switching components	No
between Ethernet and electronics	Yes
Potential separation channels	
• between the channels	No
Permissible potential difference	
Between the inputs and MANA (UCM)	10 Vpp AC
Isolation	
tested with	
• 24 V DC circuits	707 V DC (type test)
• Test voltage for interface, rms value [Vrms]	1 500 V; According to IEEE 802.3
Degree and class of protection	
IP degree of protection	IP65/67
Standards, approvals, certificates	
Suitable for applications according to AMS 2750	Yes; Declaration of Conformity, see online support entry 109757262
Suitable for applications according to CQI-9	Yes; Based on AMS 2750 E
connection method	
Design of electrical connection	4/5-pin M12 circular connectors
Dimensions	
Width	60 mm
Height	175 mm
Depth	49 mm
Weights	
Weight, approx.	930 g

last modified: 9/27/2021 