

## Analog Linear Displacement Sensor



### FEATURES

- Conductive plastic potentiometer technology. Infinite resolution
- Anodized light alloy housing
- Precious metal multi-contact wiper
- Stainless steel floating shaft
- Flange mounting
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



### QUICK REFERENCE DATA

|                  |                            |
|------------------|----------------------------|
| Sensor type      | LINEAR, conductive plastic |
| Output type      | Output by cable            |
| Market appliance | Industrial                 |
| Dimensions       | 35 mm                      |

### ELECTRICAL SPECIFICATIONS

| PARAMETER                                    |                                     |        |        |        |        |        |        |        |        |        |        |         |
|----------------------------------------------|-------------------------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|---------|
| Theoretical electrical travel (TET)          | UET - 0 mm + 2 mm                   |        |        |        |        |        |        |        |        |        |        |         |
| Independent linearity standard               | ± 0.1 %                             |        |        |        |        |        |        |        |        |        |        |         |
| Independent linearity optional               | ± 0.05 %                            |        |        |        |        |        |        |        |        |        |        |         |
| Tolerance on R <sub>n</sub>                  | ± 20 %                              |        |        |        |        |        |        |        |        |        |        |         |
| Temperature coefficient                      | -300 ± 300 ppm/°C                   |        |        |        |        |        |        |        |        |        |        |         |
| Wiper current                                | ≤ 1 mA                              |        |        |        |        |        |        |        |        |        |        |         |
| Recommended load impedance                   | ≥ 1000 R <sub>n</sub>               |        |        |        |        |        |        |        |        |        |        |         |
| Dielectric strength                          | 500 V <sub>RMS</sub> , 50 Hz, 1 min |        |        |        |        |        |        |        |        |        |        |         |
| Insulation resistance                        | ≥ 10 GΩ at 500 V <sub>DC</sub>      |        |        |        |        |        |        |        |        |        |        |         |
| Output smoothness                            | ≤ 0.05 %                            |        |        |        |        |        |        |        |        |        |        |         |
| Useful electrical travel (UET)               | 100 mm                              | 150 mm | 200 mm | 250 mm | 300 mm | 400 mm | 500 mm | 600 mm | 700 mm | 800 mm | 900 mm | 1000 mm |
| Total resistance R <sub>n</sub> (E3 series)  | 4.7 kΩ                              | 4.7 kΩ | 4.7 kΩ | 4.7 kΩ | 4.7 kΩ | 10 kΩ  | 10 kΩ  | 22 kΩ  | 22 kΩ  | 47 kΩ  | 47 kΩ  | 47 kΩ   |
| Power rating at +70 °C (0.15 W/cm of travel) | 1.5 W                               | 2.25 W | 3 W    | 3.75 W | 4.5 W  | 6 W    | 7.5 W  | 9 W    | 10.5 W | 12 W   | 13.5 W | 15 W    |

### SPECIFIC CHARACTERISTICS

| PARAMETER        |                                                                        |
|------------------|------------------------------------------------------------------------|
| Shaft version    | F = floating<br>G = guided (on request)                                |
| Connector output | S = standard (straight plug)<br>C = with right angle plug (on request) |
| Cable output     | A = axial cable sheath (on request)<br>R = radial cable (on request)   |

### MECHANICAL SPECIFICATIONS

| PARAMETER                      |                                                                           |        |        |        |        |        |        |        |        |        |        |         |
|--------------------------------|---------------------------------------------------------------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|---------|
| Mechanical travel              | UET + 3 mm min.                                                           |        |        |        |        |        |        |        |        |        |        |         |
| Driving force                  | ≤ 5 N in F version (floating shaft)<br>≤ 10 N in G version (guided shaft) |        |        |        |        |        |        |        |        |        |        |         |
| Backlash                       | < 10 μm                                                                   |        |        |        |        |        |        |        |        |        |        |         |
| Protection class               | IP 50 in F version (floating shaft)<br>IP 64 in G version (guided shaft)  |        |        |        |        |        |        |        |        |        |        |         |
| Maximum displacement speed     | 1.5 m/s                                                                   |        |        |        |        |        |        |        |        |        |        |         |
| Shaft / body misalignment      | ≤ ± 0.5 mm in F version                                                   |        |        |        |        |        |        |        |        |        |        |         |
| Mounting                       | Flanges                                                                   |        |        |        |        |        |        |        |        |        |        |         |
| Useful electrical travel (UET) | 100 mm                                                                    | 150 mm | 200 mm | 250 mm | 300 mm | 400 mm | 500 mm | 600 mm | 700 mm | 800 mm | 900 mm | 1000 mm |
| Weight                         | Shaft + wiper                                                             | 46 g   | 56 g   | 67 g   | 78 g   | 89 g   | 110 g  | 131 g  | 153 g  | 175 g  | 196 g  | 220 g   |
|                                | Sensor                                                                    | 450 g  | 540 g  | 620 g  | 720 g  | 800 g  | 970 g  | 1140 g | 1320 g | 1490 g | 1660 g | 2000 g  |

## PERFORMANCE

| PARAMETER                   |                                       |
|-----------------------------|---------------------------------------|
| Operating temperature range | -40 °C to +105 °C                     |
| Storage temperature range   | -55 °C to +125 °C                     |
| Life                        | 20M operations for UET ≤ 250 mm       |
|                             | 10M operations for 250 < UET ≤ 600 mm |
|                             | 5M operations for UET < 600 mm        |

### Note

- Nothing stated herein shall be construed as a guarantee of quality or durability.

## SAP PART NUMBERING GUIDELINES


| MODEL | USEFUL ELECTRICAL TRAVEL (mm) | SHAFT VERSION      | VALUE                                                            | LINEARITY | LEADS                           | PACKAGING |
|-------|-------------------------------|--------------------|------------------------------------------------------------------|-----------|---------------------------------|-----------|
| RH28  | 0025                          | F = floating shaft | 472 = 4K7                                                        | D = 0.1 % | S = standard<br>(straight plug) | B = box   |
|       | 0050                          |                    | 103 = 10K                                                        |           |                                 |           |
|       | 0100                          |                    | 223 = 22K                                                        |           |                                 |           |
|       | 0150                          |                    | 473 = 47K                                                        |           |                                 |           |
|       | 0200                          |                    | In accordance<br>with UET, see<br>“Electrical<br>Specifications” |           |                                 |           |
|       | 0250                          |                    |                                                                  |           |                                 |           |
|       | 0300                          |                    |                                                                  |           |                                 |           |
|       | 0350                          |                    |                                                                  |           |                                 |           |
|       | 0400                          |                    |                                                                  |           |                                 |           |
|       | 0500                          |                    |                                                                  |           |                                 |           |
|       | 0600                          |                    |                                                                  |           |                                 |           |
|       | 0700                          |                    |                                                                  |           |                                 |           |
|       | 0800                          |                    |                                                                  |           |                                 |           |
|       | 0900                          |                    |                                                                  |           |                                 |           |
|       | 1000                          |                    |                                                                  |           |                                 |           |

## ACCESSORY


|                     |                 |
|---------------------|-----------------|
| Front pivot         | ACCSRH28EPIVOTB |
| Rear pivot          | ACCSRH28MPIVOTB |
| Straight angle plug | ACCSRH28SCONNEB |
| Right angle plug    | ACCSRH28ACONNEB |

## DIMENSIONS in millimeters



### RADIAL CABLE OUTPUT VERSION (R) (WITH OPTIONAL FRONT AND REAR PIVOTS) (ON REQUEST)





### AXIAL CABLE OUTPUT VERSION (A) (ON REQUEST)



**DIMENSIONS** in millimeters

**CONNECTOR OUTPUT VERSION (WITH STRAIGHT OR RIGHT ANGLE PLUG, S OR C VERSION)**

**MOUNTING**


|                              |              |                  |                  |         |
|------------------------------|--------------|------------------|------------------|---------|
| Useful electrical travel UET | Up to 250 mm | 300 mm to 550 mm | 600 mm to 900 mm | 1000 mm |
| Number of flanges            | 4            | 6                | 8                | 10      |

**ELECTRICAL DIAGRAM**


BINDER 713 Series M12 connector (4 pin)  
for use with a 3 mm to 6 mm diameter cable  
Soldering contacts for 0.75 mm<sup>2</sup> max. wires

**OPTIONS** (on request)

- Independent linearity  $\pm 0.05$  %
- 25 mm and 50 mm electrical travels
- Front pivot
- Rear pivot (with radial cable output only)



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.